

## SMA Female to SMC Jack Adapter



## **TECHNICAL DATA SHEET**

**PE9147** 

## **SMA Female to SMC Jack Adapter**

## Configuration

Connector 1 **SMA Female** Impedance 1 50 Ohms Connector Specification 1 Mil-STD-348A SMC Jack Connector 2 Impedance 2 50 Ohms Connector Specification 2 Mil-STD-348A Adapter Design Standard Body Style Straight

## **Mechanical Specifications**

#### Size

Length, in [mm] 0.71 [18.03] Width/Dia., in [mm] 0.25 [6.35]

#### **Connector 1**

Type SMA Female
Inner Conductor Material and Plating Brass, Gold
Inner Conductor Plating Specification 3μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum
Dielectric Type Teflon

## **Connector 2**

Type SMC Jack
Inner Conductor Material and Plating Brass, Gold
Inner Conductor Plating Specification 3μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

## **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-smc-jack-straight-adapter-pe9147-p.aspx

SMA Female to SMC Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

# PE9147 CAD Drawing

SMA Female to SMC Jack Adapter

