

50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz

## **TECHNICAL DATA SHEET**

| 50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz |                          |
|----------------------------------------------------------------------------------------------------------------------|--------------------------|
| Configuration                                                                                                        |                          |
| Design                                                                                                               | Adjustable Phase Trimmer |
| Phase Adjustment, deg/GHz                                                                                            | 60                       |
| Connector 1                                                                                                          | SMA Female               |
| Impedance 1                                                                                                          | 50 Ohms                  |
| Connector 2                                                                                                          | SMA Female               |
| Impedance 2                                                                                                          | 50 Ohms                  |
| Electrical Specifications                                                                                            |                          |
| Frequency Range, GHz                                                                                                 | DC to 2                  |
| Maximum VSWR                                                                                                         | 1.5:1                    |
| Maximum Insertion Loss, dB                                                                                           | 0.5                      |
| Maximum Input Power, Watts                                                                                           | 100                      |
| Peak Power, KWatts                                                                                                   | 3,000                    |
| Mechanical Specifications                                                                                            |                          |
| Size                                                                                                                 |                          |
| Length, in [mm]                                                                                                      | 6.9 [175.26]             |
| Width/Dia., in [mm]                                                                                                  | 2 [50.8]                 |
| Height, in [mm]                                                                                                      | 1 [25.4]                 |
|                                                                                                                      |                          |
| Connector 1                                                                                                          |                          |
| Туре                                                                                                                 | SMA Female               |
| Dielectric Type                                                                                                      | PTFE                     |
| Connector 2                                                                                                          |                          |
| Туре                                                                                                                 | SMA Female               |
| Dielectric Type                                                                                                      | PTFE                     |
|                                                                                                                      |                          |
|                                                                                                                      |                          |
|                                                                                                                      |                          |
|                                                                                                                      |                          |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz PE8243

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



**PE8243** 




50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE8243 REV

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





PE8243

## TECHNICAL DATA SHEET

Compliance Certifications (visit www.Pasternack.com for current document)

Plotted and Other Data Notes:

Values at 25 °C, sea level

50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz PE8243

URL: http://www.pasternack.com/sma-female-sma-female-adjustable-phase-trimmer-dc-2-ghz-pe8243-p.aspx



PE8243 CAD Drawing

50 Ohm SMA To SMA Adjustable Phase Trimmer Operating From DC to 2 GHz With an Adjustable Phase of 60.00 Deg. Per GHz

