

High Performance Right Angle Type N Male Solder / Clamp connectors for PE-P142LL Coax



RF Connectors Technical Data Sheet

PE44816

Configuration

- N Male Connector
- 50 Ohms
- Right Angle Body Geometry
- PE-P142LL Interface Type

Features

- · Gold Platted Solder ferrules
- · Stainless Steel Interface and connector Body
- Excellent VSWR to 18 Ghz
- Tuned specifically for use with 83% VoP Tape Style

- Clamp/Solder Attachment
- 3/4 Inch Hex
- Precision Design

Low Loss Coax

- Compatible with Harbour LL142 Coax
- · Easy to assemble multi Piece design

Description

Pasternack's solder/clamp connectors designed for use with our flexible PE-P142LL Low Loss coax offer excellent performance and durability. The multi piece design has been optimized for use with Low Loss tape wrapped coax having a 83% VoP. The stainless steel construction provides for over 500 mating cycles. These connectors are compatible with LL142 coax from Harbour Industries.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.16:1	
Insertion Loss			0.42	dB
Operating Voltage (AC)			250	Vrms
Dielectric Withstanding Voltage (AC)			750	
Insulation Resistance	5,000			MOhms

Mechanical Specifications

Size

 Length
 1.2 in [30.48 mm]

 Width/Dia.
 1.14 in [28.96 mm]

 Height
 0.82 in [20.83 mm]

 Weight
 0.098 lbs [44.45 g]

Mating Torque 12 to 15 in-lbs [1.36 to 1.7 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle Precision Connector Clamp/Solder Attachment for PE-P142LL PE44816

ISO 9001 : 2008 Registered



High Performance Right Angle Type N Male Solder / Clamp connectors for PE-P142LL Coax



RF Connectors Technical Data Sheet

PE44816

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
		ASTM-B488, 50μ in. minimum
Insulation	PTFE	
Body	Passivated Stainless Steel	
		SAE-AMS-2701
Coupling Nut	Passivated Stainless Steel	
		SAE-AMS-2701

Environmental Specifications

Temperature

Operating Range -65 to 165 deg C

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant REACH Compliant

01/01/1753

Plotted and Other Data

Notes:

High Performance Right Angle Type N Male Solder /Clamp connectors for PE-P142LL Coax from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle Precision Connector Clamp/Solder Attachment for PE-P142LL PE44816

URL: http://www.pasternack.com/n-male-pe-p142ll-connector-pe44816-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.



PE44816 CAD Drawing

High Performance Right Angle Type N Male Solder / Clamp connectors for PE-P142LL Coax

