



SMC Female Bulkhead Connector Solder Attachment 0.062 inch End Launch PCB

TECHNICAL DATA SHEET

PE44848

SMC Female Bulkhead Connector Solder Attachment 0.062 inch End Launch PCB

Configuration

Connector SMC Female

Connector Interface Type 0.062 inch End Launch

Cable Attachment Method (Shield/Contact)

Body Style

Mount Method

Solder

Straight

Bulkhead

Electrical Specifications

Frequency Range, GHz DC to 10 Impedance, Ohms 50

Mechanical Specifications

Size

Length, in [mm] 0.687 [17.45] Width/Dia., in [mm] 0.3 [7.62]

Connector

Type SMC Female
Contact Material and Plating Brass, Gold
Outer Conductor Material and Plating Brass, Gold
Body Material and Plating Brass, Gold
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

SMC Female Bulkhead Connector Solder Attachment 0.062 inch End Launch PCB from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMC Female Bulkhead Connector Solder Attachment 0.062 inch End Launch PCB PE44848

URL: http://www.pasternack.com/smc-female-standard-0.062-end-launch-pcb-connector-pe44848-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44848 CAD Drawing

