

Up Converter Frequency Mixer

Level 7 (LO Power +7 dBm) 1600 to 6000 MHz

SIM-U63+



CASE STYLE: HV1195
PRICE: \$8.95 ea. QTY (10)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost
Reel Size 7" Devices/Reel 10, 20, 50, 100, 200, 500

Maximum Ratings


Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
IF Power	50mW

For extended temperature range, consult factory.
Permanent damage may occur if any of these limits are exceeded.


Pin Connections

LO	4
IF (IN)	2
RF (OUT)	8
GROUND	1,3,5,6,7

Outline Drawing



PCB Land Pattern




Suggested Layout,
Tolerance to be within ±.002

Outline Dimensions (inch)

A	B	C	D	E	F	G
.200	.180	.087	.025	.050	.028	.043
5.08	4.57	2.21	0.64	1.27	0.71	1.09
H	J	K	L	M	N	wt
.050	.030	.060	0.238	0.144	0.065	grams
1.27	0.76	1.52	6.05	3.66	1.65	0.08

Demo Board MCL P/N: TB-382 Suggested PCB Layout (PL-239)



NOTES:

- TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020" ± .0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
 - BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Features

- up converter mixer
- low conversion loss, 6.9 dB typ.
- high L-R isolation, 39 dB typ.
- ceramic, tiny size
- aqueous washable
- protected by US patent, 7,027,795

Applications

- ISM
- wide band receivers

Electrical Specifications

FREQUENCY (MHz)			CONVERSION LOSS* (dB)			LO-IF (IN) ISOLATION (dB)		LO-RF (OUT) ISOLATION (dB)		IP3 at center band (dBm)
IF (IN)	LO	RF (OUT)	Typ.	σ**	Max.	Typ.	Min.	Typ.	Min.	
1600-2500	3100-5700	3800-6000	6.9	0.3	8.4	16	10	39	29	10

1 dB Compression: +1 dBm typ.


* Conversion loss at 2400 MHz IF

** σ is a standard deviation

Typical Performance Data

Frequency (MHz)			Conversion Loss (dB)	Isolation L-I (dB)	Isolation L-R (dB)	VSWR RF (OUT) Port (:1)	VSWR LO Port (:1)
IF (IN)	LO	RF (OUT)	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm
2400.00	3100.00	5500.00	6.27	16.24	40.52	1.12	2.43
2400.00	3150.00	5550.00	6.35	16.28	40.43	1.16	2.36
2400.00	3200.00	5600.00	6.43	16.58	40.80	1.25	2.40
2400.00	3250.00	5650.00	6.61	16.60	40.95	1.34	2.32
2400.00	3300.00	5700.00	6.62	16.42	40.63	1.45	2.36
2400.00	3350.00	5750.00	6.79	16.53	40.50	1.55	2.33
2400.00	3400.00	5800.00	6.86	16.64	40.25	1.65	2.36
2400.00	3450.00	5850.00	7.07	16.71	39.98	1.66	2.38
2400.00	3500.00	5900.00	7.10	16.22	39.21	1.71	2.38
2400.00	3550.00	5950.00	7.22	16.61	39.49	1.66	2.46
2400.00	3600.00	6000.00	7.29	16.80	39.30	1.55	2.39








Electrical Schematic



Mini-Circuits®

www.minicircuits.com P.O. Box 35166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. A
M110409
SIM-U63+
ED-12399/3
DJ/TD/CP/AM
140407
Page 1 of 2



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

