


THIS DRAWING HAS BEEN GENERATED BY A CAD SYSTEM, CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY THE DESIGN ACTIVITY. DO NOT REVISE MANUALLY.

REVISIONS

REV.	DESCRIPTION	ECO	DATE	APPROVED
1	INITIAL RELEASE	I.R.	04/22/13	P.T



Specifications

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	3400		4200
Insertion Loss (dB)		< .30	.40
Isolation (dB)	20	> 22	
Return Loss (dB)	20	> 22	

Power & Temperature Ratings

Parameter	Maximum
Forward PWR Peak/AVG	500/50 Watts
Reverse Power CW	20 Watts
Termination Rating (See Note 2)	20 Watts
Operating Temperature	-20 to +85° C
Storage Temperature	-40 to +95° C

Notes:

1. Typical Values Represent Mid-Band Performance @ +23 °C.
2. Isolator Flange held to +85°C; 30 Min. maximum Duration.
3. Tab dims: 1.00[.039]Width x 2.5[.10]Length x .20[.008]Thick

CW 20W ISOLATOR MODEL: RFSL2873

<p>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS (INCHES):</p> <p>TOLERANCES ARE:</p> <table border="0"> <tr> <td>1 PLACE DECIMAL ±.2 [±.01]</td> <td>ANGULAR: ±1.0°</td> </tr> <tr> <td>2 PLACE DECIMAL ±.10 [±.004]</td> <td>SURFACE ROUGHNESS 16/</td> </tr> </table> <p>REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5</p> <p>PROPRIETARY NOTE: "THE INFORMATION CONTAINED ON THIS DOCUMENT IS CONSIDERED TO BE CONFIDENTIAL MATERIAL PROPRIETARY TO RF CIRCULATOR ISOLATOR Inc. (RFCI) AND IS PROVIDED SOLELY FOR INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE AVAILABLE TO ANY THIRD PARTY WITHOUT THE PRIOR WRITTEN CONSENT OF A RFCI OFFICIAL."</p>		1 PLACE DECIMAL ±.2 [±.01]	ANGULAR: ±1.0°	2 PLACE DECIMAL ±.10 [±.004]	SURFACE ROUGHNESS 16/	<p>THIRD ANGLE PROJECTION</p> <table border="1"> <thead> <tr> <th>APPROVALS</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>DRAWN BY: HV</td> <td>04/19/13</td> </tr> <tr> <td>CHECKED BY: P.T</td> <td>04/20/13</td> </tr> <tr> <td>DESIGN BY: P.T</td> <td>12/12/12</td> </tr> <tr> <td>ENGINEER BY: P.T</td> <td>01/15/13</td> </tr> <tr> <td>MFG. ENGR. L.T</td> <td>04/21/13</td> </tr> <tr> <td>Q.A.</td> <td></td> </tr> <tr> <td>PROG. MGMT/MKT</td> <td></td> </tr> </tbody> </table>	APPROVALS	DATE	DRAWN BY: HV	04/19/13	CHECKED BY: P.T	04/20/13	DESIGN BY: P.T	12/12/12	ENGINEER BY: P.T	01/15/13	MFG. ENGR. L.T	04/21/13	Q.A.		PROG. MGMT/MKT	
1 PLACE DECIMAL ±.2 [±.01]	ANGULAR: ±1.0°																					
2 PLACE DECIMAL ±.10 [±.004]	SURFACE ROUGHNESS 16/																					
APPROVALS	DATE																					
DRAWN BY: HV	04/19/13																					
CHECKED BY: P.T	04/20/13																					
DESIGN BY: P.T	12/12/12																					
ENGINEER BY: P.T	01/15/13																					
MFG. ENGR. L.T	04/21/13																					
Q.A.																						
PROG. MGMT/MKT																						
<p>DO NOT SCALE DRAWING</p>		<p>RFCI </p> <p>TITLE: OUTLINE/SPECS</p> <table border="1"> <tr> <td>SIZE: A</td> <td>CAGE NO.</td> <td>DWG NO. SL2873-OS</td> <td>REV. 1</td> </tr> </table>	SIZE: A	CAGE NO.	DWG NO. SL2873-OS	REV. 1																
SIZE: A	CAGE NO.	DWG NO. SL2873-OS	REV. 1																			
<p>SCALE: FULL</p>		<p>SHEET 1 OF 1</p>																				