VOA8-47/1170



Vertically Polarised Omni Antenna

The most important thing we build is trust


Designed for Ground Based Applications


Suitable for Outdoor Applications

Pattern - Omni Directional

High Gain

Rugged





Elevation	Pattern
-----------	---------

FLECTRICAL

				ELECTRICAL	
	1			Frequency	4.40 - 5.00 GHz
	Ī	<u> </u>		Gain	7.5 dBi Nom
		Ø31.50 [1.24]		Polarisation	Linear (Vertical)
		ψ31.30[1.24]		Beamwidth	360° (Az) x 17° (El) Approx
				Cross Polar	>20 dB Typ
				VSWR	2:1 Max, 1.51 Typ
	95			Power Rating	50W
	379 [14.92]			Front to Back	N/A
	379			MECHANICAL	
				Standard Finish	Drab Olive Green
	26]			Mass	274g (0.6 lbs)
	0			Temperature	-40° to +60°C
SIDE	6.50 [0.26			Wind Loading	2.0 Kg (4.4 lbs) @ 100mph
VIEW	1			MOUNTING OPTION	IS
	-	N(F) CONNECTOR		Kits Available	N/A
				See separate data sheets	
BASE VIEW	Ø 70 [2.76]	MOUNTED VIA 4 OFF Ø 5.2 HOLES EQUI SP ON 60.3mm		ADDITIONAL NOTES	5
	į.	PCD			

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

GA: 1170

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.

©European Antennas Limited

Issued 200810

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com