

Specifications


Parameter	Unit	Min	Typical	Max
Center Frequency (F0)	MHz		500	
Bandwidth (B)	MHz		180	
-3 dB Bandwidth (B3)	MHz	191	193.7	
-40 dB Bandwidth (B40)	MHz		219.9	226
Delay (T0)	μsec	0.58	0.584	0.59
Insertion Loss (IL)	dB		32	34
Amplitude Ripple	dB p-p		0.5	1
Phase Ripple	deg p-p		5.7	12
Rejection	dB	44	53	
Spurious for $ t-T0 > .9T0$	dB		-50	-40
Substrate Material	YZ-LN			

Notes:

- Center Frequency (F0) and Bandwidth (B) are defined, not measured.
- Insertion Loss is the minimum loss for $|f-F0| < .5B$
- Ripple spec applies to the $|f-F0| < .4B$, and is doubled for $.4B < |f-F0| < .5B$
- Rejection spec applies to $(B40 \text{ Spec} - B/2) < |f-F0| < F0/2$
- Specifications are at 22C only. Unit will operate undamaged from -54C to 125C with shifts $dF0 = -x \cdot F0$, $dT0 = x \cdot T0$, where $x = 94E-6 \cdot (\text{temperature} - 22C)$


Typical Performance

Frequency Response
(Best Fit Linear Phase Removed)




Impulse Response


FFT(Frequency Response * Cos(0.5*PI*MIN(1, MAX(0, |f-F0|*2.0/B-1.0))))^2



Package Outline



Matching



Matched S-parameters available at www.phonon.com