


Coaxial Power Splitter/Combiner

48 Way-0° 50Ω 10 to 300 MHz

ZFSC-48-1



Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.87W max.
Permanent damage may occur if any of these limits are exceeded.	

Coaxial Connections

SUM PORT	S (COM)
PORT 1,2,3,4.....,48	1,2,3,4.....,48

Features

- good isolation, 28 dB typ.
- rugged shielded case

Applications

- HF/VHF
- instrumentation
- test set-ups

BNC version shown

CASE STYLE: HH68

Connectors	Model
BNC	ZFSC-48-1
SMA	ZFSC-48-1-S

Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)						INSERTION LOSS (dB) ABOVE 16.8 dB						AMPLITUDE UNBALANCE (dB)		
	L		M		U		L		M		U		L	M	U
f_L - f_U	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Max.	Max.	Max.
10-300	30	25	28	20	23	20	1.2	2.0	2.1	2.5	2.8	4.0	0.8	0.9	1.2


L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Freq. (MHz)	Total Loss ¹ (dB)	Amplitude Unbalance (dB)	Isolation (dB)		VSWR S	VSWR OUTPUT
			Adjacent	Opposite		
10.00	17.71	0.27	34.97	56.49	1.11	1.21
30.00	17.81	0.25	34.32	56.28	1.06	1.20
51.00	17.88	0.31	31.99	54.74	1.02	1.19
100.00	18.04	0.47	28.18	51.27	1.10	1.16
120.00	18.13	0.54	27.25	49.83	1.15	1.14
140.00	18.22	0.57	26.52	48.59	1.21	1.12
145.00	18.23	0.58	26.40	48.27	1.22	1.12
150.00	18.24	0.58	26.28	47.89	1.24	1.12
160.00	18.24	0.57	26.08	47.49	1.26	1.11
170.00	18.29	0.56	25.95	47.06	1.29	1.11
180.00	18.40	0.53	25.90	46.59	1.31	1.10
190.00	18.51	0.50	25.86	46.13	1.33	1.10
200.00	18.56	0.47	25.86	45.71	1.35	1.10
250.00	18.91	0.50	26.62	44.13	1.40	1.13
300.00	19.17	0.82	28.40	42.37	1.37	1.18




1. Total Loss = Insertion Loss + 16.8dB splitter loss.

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
9.31	1.60	3.57	8.84	.25	.88	.36	.160
236.47	40.64	90.68	224.54	6.35	22.35	9.14	4.06
J	K	L	M	N	P	Q	wt
.34	.69	.54	.66	8.34	.33	.06	grams
8.64	17.53	13.72	16.76	211.84	8.38	1.52	1090.0



electrical schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. C
M151107
ZFSC-48-1
HY/TD/CP/AM
151020