

# F

# SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz

# TECHNICAL DATA SHEET

PE44780

Pasternack 8 GHz SMP connectors are designed to offer a low cost alternative where the SMP form factor is desired but the standard SMP frequency range is not needed. The line of 8 GHz SMP connectors is fully compatible with industry standard SMP and GPO® connectors. These SMP connectors offer a low cost high performance blind-mate solution for lower frequency applications. The Male versions of the 8 GHz SMP is available in Full Detent, Limited Detent, and Smooth Bore versions.

- Fully compatible with industry standard SMP and GPO® connectors
- Full Detent, Limited Detent, and Smooth Bore Male designs
- Glass Bead Hermetic Sealed Male Shroud versions available
- DC to 8 GHz with excelent VSWR and RF Leakage performance

## Configuration

Connector SMP Male, Limited Detent

Connector Specification MIL-STD-348A

Connector Interface Type Pin
Cable Attachment Method (Shield/Contact) Solder

Body Style Straight
Isolated Ground / Hermetic Hermetically Sealed

**Electrical Specifications** 

Frequency Range, GHz DC to 8 Impedance, Ohms 50 Maximum VSWR 1.1:1

**Mechanical Specifications** 

**Body Plating Specification** 

**Temperature** 

Operating Range, deg C -55 to +155

Size

Length, in [mm] 0.192 [4.88] Width/Dia., in [mm] 0.146 [3.71]

Connector

Type SMP Male
Mating Cycles 500
Contact Material and Plating Kovar, Gold
Contact Plating Specification MIL-DTL-45204
Body Material and Plating Kovar, Gold

Dielectric Type Glass

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz PE44780

MIL-DTL-45204

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered





# SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz

# TECHNICAL DATA SHEET

PE44780

### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level GPO® is a Registered Trademark of Corning Gilbert Inc.

SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz PE44780

URL: http://www.pasternack.com/smp-male-standard-thru-hole-pcb-connector-pe44780-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE44780 CAD Drawing

SMP Male Limited Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Half Shroud Full Body, Up To 8 GHz

