

## **Specifications**

Parameter	Minimum	Typical	Maximum
Frequency Range (MHz)	2130		2280
Insertion Loss (dB)		< .20	.30
Isolation (dB)	22	> 25	
Return Loss (dB)	22	> 25	

## Notes:

- 1. Typical Values Represent Mid-Band Performance @ +23 °C.
- 2. Iso-Attenuator Flange held to +85°C; 30 Min. maximum Duration.
- 3. Tab dims: 1.00[.039]Width x 2.5[.10]Length x .20[.008]Thick

## Power & Temperature Ratings

Parameter	Maximum			
Forward PWR Peak/AVG	1000/100 Watts			
Reverse Power CW	100 Watts			
Attenuator Rating (See Note 2)	100 Watts			
Attenuation (P3)	30dB±1dB			
Operating Temperature	-40 to +85° C			
Storage Temperature	-40 to +95° C			

## CW 100W-30dB ISO-ATTENUATOR MODEL: RFSL2736-A30

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS [INCHES]:  TOLERANCES ARE:		THIRD ANGLE PROJECTION								
1 PLACE DECIMAL ±.2 [±.01] 2 PLACE DECIMAL ±.10 [±.004]	ANGULAR: ±1.0° SURFACE ROUGHNESS 16/	APPRO	VALS	DATE						
REMOVE ALL BURRS AND BREAK SHARP EDGES. SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1 DIMENSIONING & TOLERANCING IN ACCORDANCE WITH LATEST ANSI Y14.5		DRAWN BY:	HV	04/19/13						
		CHECKED BY:	P.T	04/20/13	TITLE					
INFORMATION PURPOSES. THIS INFORMATION SHALL NOT BE USED BY ANYONE OTHER THAN RFCI TO DESIGN OR CONSTRUCT ANY OF THE ITEMS DEPICTED, NOR SHALL IT BE DISCLOSED, DUPLICATED, OR COPIED FOR ANY PURPOSE, NOR MADE		DESIGN BY:	P.T	12/12/12	OUTLINE/SPECS					
		ENGINEER BY:	P.T	01/15/13	OOTEINE/OFEOO					
		MFG. ENGR.	L.T	04/21/13	SIZE	CAGE NO.	DWG NO.			TREV.
		Q.A.						6 40	0.00	4
		PROG. MGMT/MKT	•		Α		SL2736-A30-OS		0-03	<b>"</b>
DO NOT SCALE	DRAWING			SCALE: FULL				SHEET 1 OF 1		
				<b>A</b>				•		