

## SMA Female to SSMA Female Adapter



## **TECHNICAL DATA SHEET**

PE9399

## **SMA Female to SSMA Female Adapter**

## Configuration

Connector 1SMA FemaleImpedance 150 OhmsConnector 2SSMA FemaleImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

## **Mechanical Specifications**

#### Size

Length, in [mm] 0.748 [19] Width/Dia., in [mm] 0.25 [6.35]

#### **Connector 1**

Type SMA Female
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

#### **Connector 2**

Type SSMA Female Inner Conductor Material and Plating Gold Body Material and Plating Brass, Nickel Dielectric Type PTFE

## Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

## **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-ssma-female-straight-adapter-pe9399-p.aspx

SMA Female to SSMA Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# **PE9399 CAD Drawing**SMA Female to SSMA Female Adapter

