



AMP1055 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	800 - 2500MHz	
Power Output	200 Watt Min / 250 Watt Typ	CW
Power Gain	53 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30dBc Typ	43 dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	>20 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc	
Operating Voltage	30 -32 VDC	
Current Consumption	20 Amp Max	At rated Pout
Max Input Power	+10dBm	Without damage
Load VSWR Protection	$\infty : 1$	
Turn On / Off Speed	5 μSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS


Parameter	Specification	Notes
Dimensions	220 X 146 X 27 mm	Excluding Connectors
Weight	1525 gr.	Max Weight
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	7-Pin Hybrid D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB HYBRID CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	OPTION 101 - Forward power detect
2	VVA	OPTION 103 - Variable Voltage Attenuator
3	CURRENT SENSOR	$I_D @ 20\text{mV}/100\text{mA}$ Typ
4	TEMP SENSOR	$V_T @ 10\text{mV}/^\circ\text{C} + 500\text{mV}$ Typ
5	SHUTDOWN	TTL
A1	VDD	32VDC
A2	GND	Ground

AMP1055 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING - OPTION 101



OPTION ORDERING INFORMATION:

OPTION	Function	Description
101	FWD	Forward power detect
103	VVA	Variable Voltage Attenuator