



## SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz

### TECHNICAL DATA SHEET

PE44779

Pasternack 8 GHz SMP connectors are designed to offer a low cost alternative where the SMP form factor is desired but the standard SMP frequency range is not needed. The line of 8 GHz SMP connectors is fully compatible with industry standard SMP and GPO® connectors. These SMP connectors offer a low cost high performance blind-mate solution for lower frequency applications. The Male versions of the 8 GHz SMP is available in Full Detent, Limited Detent, and Smooth Bore versions.

- Fully compatible with industry standard SMP and GPO® connectors
- Full Detent, Limited Detent, and Smooth Bore Male designs
- Glass Bead Hermetic Sealed Male Shroud versions available
- DC to 8 GHz with excelent VSWR and RF Leakage performance

### Configuration

Connector SMP Male, Full Detent

Connector Specification MIL-STD-348A

Connector Interface Type Pin
Cable Attachment Method (Shield/Contact) Solder

Body Style Straight

Isolated Ground / Hermetic Hermetically Sealed

### **Electrical Specifications**

Frequency Range, GHz

Impedance, Ohms

Maximum VSWR

DC to 8

50

1.1:1

### **Mechanical Specifications**

**Temperature** 

Operating Range, deg C -55 to +155

Size

Length, in [mm] 0.25 [6.35] Width/Dia., in [mm] 0.165 [4.19]

Connector

Type SMP Male Mating Cycles 100

Contact Material and Plating
Contact Plating Specification
Body Material and Plating
Body Plating Specification

Kovar, Gold
Kovar, Gold
MIL-DTL-45204
MIL-DTL-45204

Dielectric Type Glass

### Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz PE44779

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered



# PA GORK

## SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz

### TECHNICAL DATA SHEET

PE44779

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level GPO® is a Registered Trademark of Corning Gilbert Inc.

SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz PE44779

URL: http://www.pasternack.com/smp-male-standard-thru-hole-pcb-connector-pe44779-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE44779 REV 1.2



ISO 9001 : 2008 Registered

### PE44779 CAD Drawing

SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz

