

HYBRID COUPLER

PART NO. : WVH-2X2-N-02

◆ APPLICATION

> 698MHz ~ 2700MHz Band System

◆ FEATURE

> High Reliability
> **RoHS Compliant**

◆ ELECTRICAL SPECIFICATION

ITEM	SPECIFICATION
Frequency Range (MHz)	698 ~ 2700
Splitter Loss	3.0dB
Insertion Loss	0.15dB
Coupling Tolerance	±0.5dB
Isolation	25.0dB Min
VSWR	1.2:1 Max
Intermodulation production	-150dBc @ +43dBm 2 tone
Power handling per input port	80W Max
In/Out Impedance	50 Ohms Nominal

◆ ENVIRONMENTAL SPECIFICATIONS

ITEM	SPECIFICATION
Operating Temperature Range	-30°C to +75°C , IP65

◆ MECHANICAL SPECIFICATIONS

ITEM	SPECIFICATION
Dimension	126.0 x 46.0.0 x 22.0 Max (Unit:mm)
Mounting Points	See Outline Drawing
RF Connector	Input & Output Ports : N Female Connector
Connector Position	See Outline Drawing
Finish	Gray Color Epoxy Coating

HYBRID COUPLER

◆ OUTLINE DRWAING

