

Low Pass Filter

SXLP-4.7+

50Ω DC to 4.7 MHz

Maximum Ratings

Operating Temperature -40°C to 85°C

Storage Temperature -55°C to 100°C

RF Power Input 0.5W Max.

Permanent damage may occur if any of these limits are exceeded.


Pin Connections

INPUT 1

OUTPUT 8

GROUND 2, 3, 4, 5, 6, 7

Outline Drawing




Outline Dimensions (inch mm)

A	B	C	D	E	F
.44	.74	.27	.200	.07	.060
11.18	18.80	6.86	5.08	1.78	1.52
G	H	J	K	L	M
.040	.660	.200	.470	.055	.060
1.02	16.76	5.08	11.94	1.40	1.52
					grams
					3.0

Demo Board MCL P/N: TB-368




Suggested PCB Layout (PL-230)



NOTE:

1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS: .025"±.002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK




Features

- high rejection
- sharp cut-off
- shielded package
- aqueous washable
- low cost

Applications

- defense communications
- receivers / transmitters
- harmonic rejection



CASE STYLE: HF1139
PRICE: \$ 8.95 ea. QTY (1-9)


+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Low Pass Filter Electrical Specifications (T_{AMB} = 25°C)

PASSBAND (MHz)	f _{co} , MHz Nom.	STOPBAND (MHz)	VSWR (:1)
(Loss < 1dB)	(Loss 3dB)	(Loss > 20dB) (Loss > 40dB)	Passband Typ. Stopband Typ.
DC - 4.7	5.6	6.6 - 7.4 7.4 - 600	1.25 18

Typical Frequency Response



Functional Schematic



Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)	Frequency (MHz)	Group Delay (nSec)
$\bar{x}$	σ			
0.5	0.08	0.01	0.5	132.84
2.7	0.20	0.01	1.2	117.19
2.7	0.20	0.01	1.4	120.85
4.5	0.49	0.02	1.6	124.16
4.7	0.56	0.02	1.8	124.15
5.3	1.02	0.04	2.0	127.50
5.6	2.09	0.32	2.5	131.07
5.8	4.70	0.75	3.0	142.83
6.0	9.43	1.03	3.5	160.70
6.2	15.17	1.09	4.0	182.44
6.6	27.16	1.10	4.5	223.68
7.4	57.30	1.96	4.7	245.95
15.0	52.02	0.24	4.8	255.31
23.0	61.33	0.16	5.0	295.98
40.0	69.54	0.59	5.2	352.27
100.0	65.17	0.41	5.3	385.52
200.0	57.06	0.25	5.4	438.20
400.0	58.40	0.26	5.5	484.24
600.0	55.96	0.30	5.6	521.62

Mini-Circuits®

ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

REV. OR
M112220
EDR-7478/1U
SXLP-4.7+
URJ/RAV
121015
Page 1 of 1

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.