



## 50 Ohm 5 Watts Passivated Stainless Steel N Female RF Load Up To 18 GHz

## **TECHNICAL DATA SHEET**

PE6098

## 50 Ohm 5 Watts Passivated Stainless Steel N Female RF Load Up To 18 GHz

Configuration

Connector N Female
Connector Specification MIL-C-39012

Heat Sink Aluminum Heatsink, Black Anodized

**Electrical Specifications** 

Frequency Range, GHz DC to 18
Impedance, Ohms 50
Maximum VSWR 1.25:1
Maximum Input Power, Watts 5

## **Mechanical Specifications**

Size

Length, in [mm] 1.235 [31.37] Width/Dia., in [mm] 0.625 [15.88]

Connector

Type N Female

Body Material and Plating Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

50 Ohm 5 Watts Passivated Stainless Steel N Female RF Load Up To 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 5 Watts Passivated Stainless Steel N Female RF Load Up To 18 GHz PE6098

URL: http://www.pasternack.com/n-female-high-power-termination-pe6098-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



