

522 to 524MHz – Band Pass Filter

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics


Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYBPF9191A522T524NF	522 ~ 524	1.5	1.45	40dB @27-497MHz 40dB @551MHz 65dB @1000-2900MHz 85dB @3200-4000MHz	100	N-F	-40 ~ +85
UIYBPF9191A522T524SF	522 ~ 524	1.5	1.45	40dB @27-497MHz 40dB @551MHz 65dB @1000-2900MHz 85dB @3200-4000MHz	100	SMA-F	-40 ~ +85

² Listed are specific frequency ranges and other ranges are available.

² Please provide the below informations when inquiring and mark * is required.

- * 1. The specific pass band frequency range
- * 2. The specific rejection and frequency
- 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ± 0.2 mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com