

MHV Male to SHV Jack Adapter



TECHNICAL DATA SHEET

PE9335

MHV Male to SHV Jack Adapter

Configuration

Connector 1MHV MaleImpedance 150 OhmsConnector 2SHV JackImpedance 250 OhmsAdapter DesignStandardBody StyleStraight

Mechanical Specifications

Size

Length, in [mm] 1.65 [41.91] Width/Dia., in [mm] 0.57 [14.48]

Connector 1

Type MHV Male
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Connector 2

Type SHV Jack
Inner Conductor Material and Plating Silver
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/mhv-male-shv-jack-straight-adapter-pe9335-p.aspx

MHV Male to SHV Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9335 CAD Drawing

MHV Male to SHV Jack Adapter

