

## N Male Right Angle Connector Crimp/Solder Attachment For RG214, RG9, RG225, RG393



## TECHNICAL DATA SHEET

PE4483

## N Male Right Angle Connector Crimp/Solder Attachment For RG214, RG9, RG225, RG393

Configuration

Connector N Male

Connector Specification MIL-STD-348A

Connector Interface Type RG214,RG9,RG225,RG393

Cable Attachment Method (Shield/Contact)

Crimp/Solder

Body Style

Right Angle

**Electrical Specifications** 

Frequency Range, GHz

Impedance, Ohms

Maximum Operating Voltage, Volts

Dielectric Withstanding Voltage, Vrms

DC to 11

1,000

1,000

2,500

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.99 [50.55]

 Width/Dia., in [mm]
 0.8 [20]

 Height, in [mm]
 1.29 [32.77]

 Weight, lbs [g]
 0.151 [68.49]

Connector

Type N Male
Contact Material and Plating Brass, Gold
Coupling Nut Material and Plating Brass, Nickel
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/n-male-standard-rg214-rg9-rg225-rg393-connector-pe4483-p.aspx

N Male Right Angle Connector Crimp/Solder Attachment For RG214, RG9, RG225, RG393 from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

