

Optical Clock Recovery

Model HV71T-3
Model HV71SM-32
2.488 MHz






Electrical Specifications:⁽¹⁾

Parameter	Specifications
Frequency Range	2.488 GHz
Power Output at 25°C (50 Ohm load)	+10 dBm, min.
Power Output Variation vs. Temperature	1.0 dB, typical
Frequency Drift vs. Temperature ⁽²⁾	70 MHz, typical
Frequency Pulling (12 dB Return Loss)	30 MHz, typical
Frequency Pushing	8 MHz/V, typical
Tuning Voltage Limits	+4 to +8 VDC
SSB Phase Noise (50 kHz offset)	-87 dBc/Hz, typical
Harmonics ⁽³⁾	-15 dBc, typical
Spurious	-60 dBc, max.
Bias Voltage ⁽⁴⁾	+12 VDC ±1%
Bias Current ⁽⁵⁾	55 mA, typical
Operating Temperature	0 to +85 °C

Notes:

1. Specifications guaranteed over the operating temperature range. Those specifications indicated as typical are not guaranteed. Plots exemplify typical performance at +25°C
2. Total frequency drift over the full temperature range.
3. Worst case harmonics over the frequency range.
4. Alternate bias voltages available.
5. Lower bias current available.
6. Military screening available.

Typical Performance at 25°C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, FL 32905 · PH (888) 553-7531 · Fax (888) 553-7532

www.SpectrumMicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, PA 19154 · PH (215) 464-4000 · Fax (215) 464-4001