

300 to 1300MHz – Dual Junction Drop in Circulator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss (1-2) Max(dB)	Isolation (2-1) Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYDDC7038A309T339	309 ~ 339	1.0	40	1.25	300	300	TAB	-20 ~ +65
UIYDDC7038A350T370	350 ~ 370	0.6	45	1.2	300	300	TAB	-20 ~ +65
UIYDDC7038A390T410	390 ~ 410	0.6	45	1.2	300	300	TAB	-30 ~ +70
UIYDDC7038A400T470	400 ~ 470	1.0	40	1.25	300	300	TAB	-30 ~ +70
UIYDDC7038A440T470	440 ~ 470	0.6	45	1.2	300	300	TAB	-30 ~ +70
UIYDDC7038A470T570	470 ~ 570	0.7	38	1.25	300	300	TAB	-20 ~ +65
UIYDDC7038A570T670	570 ~ 670	0.8	40	1.25	300	300	TAB	-20 ~ +65
UIYDDC7038A670T770	670 ~ 770	0.8	40	1.25	300	300	TAB	-20 ~ +65
UIYDDC7038A770T860	770 ~ 860	0.7	45	1.2	300	300	TAB	-20 ~ +65
UIYDDC7038A600T800	600 ~ 800	1.0	36	1.3	300	300	TAB	-30 ~ +70

² List are specify frequency range and other ranges available.


² Please enter below information when inquiry and mark * is must.

* 1. The specific frequency range

* 2. Power handling (Forward, Reverse, Peak, etc.)

3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ± 0.2 mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com