


9900 Series Frequency Converters

C, Ku, and DBS Bands



The MITEQ frequency converters are designed for advanced satellite communication systems and are available for a wide variety of frequency plans. Phase noise, amplitude flatness and spurious outputs have been optimized to provide the user with a transparent frequency conversion for all video and data applications.

A strong feature set of monitor and control functions supports powerful local and remote control. Among the features are control of frequency, attenuation and 64 memory locations for each converter where various setups can be stored and recalled.

A continuously updated log of time-stamped records of activity is also provided.

Features

- Supports expandable NSU 1:N Switchover Series (D-323)
- Amplitude slope adjust
- Three monitor and control ports:
 1. RS485/RS422 remote interface (J6A) changes to RS232 with Option 17C
 2. RS485/RS422 control interface (J7) is provided for use with NSU redundancy system (D-323) or as an alternative interface
 3. 10/100Base-T Ethernet interface (J6B)
- RF, IF and LO monitor ports
- Automatic switching to external 5/10 MHz reference and electronic adjust of internal reference frequency
- Low intermodulation distortion
- Better than IESS-308/309 compliant phase noise
- 64 programmable memory locations
- 30 dB level control
- External alarm input via contact closure
- Date and time-stamped event log
- CE Mark

Options


- Higher stability reference
- Remote RS232
- 140 MHz IF frequency
- 50 ohm IF impedance
- Type "N" RF connector

RF Frequency (GHz)	Model Numbers
Upconverters	
5.725 - 6.725	U-9953-6-1K
12.75 -14.5	U-9956-7-1K
13.75 -14.8	U-9956-6-1K
17.3 -18.4	U-9957-2-1K
Downconverters	
3.4 - 4.2	D-9901-1-1K
10.7 - 12.75	D-9908-6-1K

Specifications	Upconverter	Downconverter
Type	Dual conversion	
Frequency step size	1 kHz	
Frequency sense	No inversion	
Input characteristics		
Frequency	70 \pm 20 MHz (140 \pm 40 MHz Option 4)	Refer to model number table
Impedance	75 ohms (50 ohms Option 15)	50 ohms
Return loss	26 dB minimum (70 \pm 20 MHz), 20 dB minimum (140 \pm 40 MHz)	20 dB minimum
Signal monitor	-20 dBc nominal	
Input level (non-damage)	+15 dBm maximum	
Output characteristics		
Frequency	Refer to model number table	70 \pm 20 MHz (140 \pm 40 MHz Option 4)
Impedance	50 ohms	75 ohms (50 ohms Option 15)
Return loss	20 dB minimum	26 dB minimum (70 \pm 20 MHz), 20 dB minimum (140 \pm 40 MHz)
Signal monitor	-20 dBc nominal	
Power output (P1 dB)		
C-band	+16 dBm minimum/17 dBm typical	
Ku-band	+10 dBm minimum/12 dBm typical	+16 dBm minimum/17 dBm typical
Transfer characteristics		
Gain	+31–34 dB at 23°C	+44–48 dB at 23°C
Noise figure at min. atten.	14 dB maximum	11 dB maximum
Noise power density	-125 dBm/Hz maximum	N/A
Image rejection	N/A	80 dB minimum
Level stability	\pm 0.25 dB/day maximum at constant temperature, \pm 0.5 dB typical from 0 to 50°C	
Amplitude response	\pm 0.3 dB maximum/40 MHz, \pm 0.45 dB maximum/80 MHz (140 \pm 40 MHz Option 4)	
Slope adjust	\pm 1 dB typical in 0.2 dB steps	
Group delay (70 \pm 18 MHz)		
Linear	0.03 ns/MHz maximum (15 to 50°C)	
Parabolic	0.01 ns/MHz ² maximum (15 to 50°C)	
Ripple	1 ns peak-to-peak maximum	
Group delay (140 \pm 36 MHz)		
Linear	0.025 ns/MHz maximum (15 to 50°C)	
Parabolic	0.0035 ns/MHz ² maximum (15 to 50°C)	
Ripple	1 ns peak-to-peak maximum	
Intermodulation distortion (third order)	Two signals each at 0 dBm output,	
C-band	55 dBc minimum (+27.5 dBm OIP3 pt.)	60 dBc minimum (+30 dBm OIP3 pt.)
Ku-band	45 dBc minimum (+22.5 dBm OIP3 pt.)	60 dBc minimum (+30 dBm OIP3 pt.)
AM/PM conversion	0.1°/dB maximum to 0 dBm output	
Gain slope	0.03 dB/MHz typical, 0.05 dB/MHz maximum (10 MHz minimum)	
Frequency stability	\pm 2 \times 10 ⁻⁸ , 0 to 50°C (higher stability options available), \pm 5 \times 10 ⁻⁹ /day typical (fixed temperature after 24 hour on time)	
Frequency accuracy	C-band: \pm 10 Hz, Ku-band: <1 Hz, maximum using external reference, DBS-band: <1 Hz	
Spurious outputs		
Signal related	65 dBc up to 0 dBm output	
Signal independent	-80 dBm maximum	
LO leakage at RF port	-75 dBm maximum	-80 dBm maximum
Gain adjustment	30 dB in 0.2 dB steps	
Upconverter mute	80 dB minimum	N/A
External reference	5 or 10 MHz, +4 \pm 3 dBm Unit will automatically switch to internal reference if external reference level falls below +1 dBm nominal	
Phase noise	See chart	
Remote interface	RS485/RS422: 2 ports user selectable each port (1 port with Option 17C) Ethernet interface: HTTP based web server, SNMP 1.0 configuration, Alarm reporting via SNMP trap, Telnet access, Password protection	

Note: All specifications guaranteed at maximum gain unless otherwise noted.

Representative Block Diagrams



Phase Noise Specifications - Offset [Hz]

1. Phase noise (-dBc/Hz) (maximum/typical with internal reference).

Upconverters							
Model	10	100	1K	10K	100K	300K	1M
U-9953-6-1K	63/69	80/85	95/97	97/100	97/104	97/106	115/123
U-9956-6-1K	50/71	66/85	87/93	91/96	93/98	93/104	111/122
U-9956-7-1K	50/70	66/84	85/93	90/95	93/96	93/102	111/122
U-9957-2-1K	50/70	66/83	85/91	90/93	93/96	93/101	111/120
Downconverters							
D-9901-1-1K	63/69	80/83	95/97	97/99	97/103	97/106	115/123
D-9908-6-1K	51/68	69/82	87/92	91/96	93/97	93/106	111/122

Maximum External Reference To Achieve Above Phase Noise with 10 MHz Reference (dBc/Hz)

	10	100	1K	10K	100K	300K	1M
Systems without Option 31, 10E, 10F, 10G or 10H	120	150	160	160	160	160	160
Systems with Option 10E, 10F, 10G or 10H	95	130	140	140	140	140	140

Options

4. 140 MHz IF frequency.

10. Higher frequency stability reference.

C. $\pm 2 \times 10^{-9}$, 0 to 50°C, 1×10^{-9} /day typical (fixed temperature after 24 hour on time).

E. $\pm 5 \times 10^{-9}$, 0 to 50°C, 1×10^{-9} /day typical (fixed temperature after 24 hour on time). See Note 1 below.

F. $\pm 2 \times 10^{-9}$, 0 to 50°C, 1×10^{-9} /day typical (fixed temperature after 24 hour on time). See Note 1 below.

NOTE 1: Analog reference Phase Lock: External 5 or 10 MHz at +4 ± 3 dBm. If external reference is below +1 dBm nominal, the converter will automatically lock to the internal reference. Reference oscillator acts as an analog phase lock with a 0.1 Hz nominal loop bandwidth. Typical loop suppression of the external reference is as follows: 28 dB at 1 Hz offset; 65 dB at 10 Hz offset and 100 dB at 100 Hz offset.

G. Self calibrating tracking reference with controlled slew rate. Internal reference tracks external reference and uses external reference to correct for aging of the internal reference. The internal reference changes frequency at a maximum rate of 0.06 ppm/second. When external reference is lost, the reference frequency is held at the previous value. Frequency stability on internal reference: $\pm 5 \times 10^{-8}$, 0 to 50°C, 1×10^{-9} /day typical (fixed temperature after 72 hour on time). 5×10^{-8} /year typical

H. Self calibrating tracking reference with controlled slew rate. Internal reference tracks external reference and uses external reference to correct for aging of the internal reference. The internal reference changes frequency at a maximum rate of 0.06 ppm/second. When external reference is lost, the reference frequency is held at the previous value. Frequency stability on internal reference: $\pm 2 \times 10^{-9}$, 0 to 50°C, 1×10^{-9} /day typical (fixed temperature after 72 hour on time). 5×10^{-8} /year typical

Options

15. 50 ohm IF impedance.

17. Remote control.

C. RS232 remote interface.

NRF. Type N-female RF connector (Note: Monitor remains SMA female). RF return loss: 18 dB.

Notes: Missing option numbers are not applicable for this product. For literature describing Local control (front panel) and remote control (bus protocols), refer to MITEQ's Technical Note 25T063.

Protocols are backwards compatible with Technical Notes 25T010 and 25T009.

General Specifications

Primary Power Requirements

Voltage 100-240 VAC (-10%, +6%)
 Frequency 47-63 Hz
 Consumption 55 W typical, 65 W maximum

Physical

Weight 12 pounds (5.4 kg) nominal
 Chassis dimensions 19" [482.6mm] x 1.75" [44.45mm] panel height x 22" [560mm] maximum
 (including connectors)

Connectors

RF SMA female (N female, Option NRF)
 RF monitor SMA female
 IF BNC female
 IF monitor BNC female
 LO monitors SMA female
 Alarm DE-9P
 External reference BNC female
 Remote interface DE-9S for RS485, RS422 and RS232,
 RJ-45 female for Ethernet
 Primary power input IEC-320
 Auxiliary control interface DE-9S

Environmental

Operating

Ambient temperature 0 to 50°C
 Relative humidity Up to 95% at 30°C
 Atmospheric pressure Up to 10,000 feet

Nonoperating

Ambient temperature -50 to +70°C
 Relative humidity Up to 95% at 40°C
 Atmospheric pressure Up to 40,000 feet
 Shock and vibration Normal handling by commercial carriers

Typical Rear Panel View



RSM Switch Module Location
 (see D-323 for more information)