



5300 Beethoven Street, Los Angeles, CA 90066  
TEL: (310)306-5556 • FAX: (310)577-9887  
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## MODEL 5048R-900

0.15 - 230 MHz

75 WATTS

LINEAR POWER RF AMPLIFIER

### Solid State Broadband High Power RF Amplifier

The 5048R-900 is a 75 Watt broadband amplifier that covers the 0.15 – 230 MHz frequency range. This amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5048R-900 comes with an extended multiyear warranty.

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	0.15 – 230 MHz
2	Saturated Output Power	75 Watts typical
3	Power Output @ 1dB Comp.	45 Watts min
4	Small Signal Gain	+49 dB min
5	Gain Flatness	± 1.5 dB max
6	IP <sub>3</sub>	+52 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-15 dBc typical @ 45 Watts
9	Spurious Signals	< -60 dBc typical @ 45 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	500 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	0 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<b>Mechanical</b>		
16	Dimensions	19" x 5.25" x 20"
17	Weight	48 lb. max
18	Connectors	Rear Panel, Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
<b>Environmental</b>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.

### CIRCUIT PROTECTIONS

- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

### FEATURES

- ◇ Customer Specific Front Panel
- ◇ Rear Panel Mounted DB9-Female for External RF Enable / Standby Control

NOTE: Pin **5** is GND, Pin **1** is the Control Line.

- IF Pin 1: OPEN - RF Standby Condition (Nominal Gain - 30dB min.)

- IF Pin 1: GND - RF Enabled (Amplifier in Normal Operation) ( < 100mA to Activate )