


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED




Specifications:

Frequency Range: 0.9–1.75 GHz
Attenuation: 15dB
Insertion Loss: 0.5 Max.
VSWR: 1.70:1
RF Power: 7W Average, 3kW Peak

Environmental:

Temperature range: –55°C to +110°C
Shock: 15 G's, 11mS, 1/2 sine
Vibration: 3 G's overall
Altitude: 40,000 ft. Survival 25,000ft Operating

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A	
				SHEET: N/A	
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: ± 1/64 DECIMALS: ±0.01 ±0.005 ANGLE: ±1/2°		DRAWING TITLE: CONTINUOUSLY VARIABLE ATTENUATOR WITH DIAL	
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI) THIRD ANGLE PROJECTION 		PART NO. CVA2-15/D	
				CAGE CODE: 0D2L5	
				DRAWN: Paiboon Luekhamhan	
APPROVED: T. Nguyen		DATE: 02-08-2011		DO NOT SCALE THE DRAWING	