

250 to 1500MHz – Coaxial Circulator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ Military, space and commercial applications.
- ◆ Guaranteed for one year standard.
- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.

RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYCC4550A250T260NF	250 ~ 260	0.6	20	1.25	300	300	N-F	-30 ~ +70
UIYCC4550A289T359NF	289 ~ 359	0.5	20	1.25	300	300	N-F	-30 ~ +70
UIYCC4550A300T400SF	300 ~ 400	0.7	18	1.3	100	100	SMA-F	-30 ~ +70
UIYCC4550A350T400SF	350 ~ 400	0.35	23	1.2	100	100	SMA-F	-30 ~ +70
UIYCC4550A350T500SF	350 ~ 500	0.6	16	1.4	100	100	SMA-F	-20 ~ +60
UIYCC4550A400T430NF	400 ~ 430	0.25	25	1.15	300	300	N-F	-30 ~ +70
UIYCC4550A440T470NF	440 ~ 470	0.25	25	1.15	300	300	N-F	-30 ~ +70
UIYCC4550A400T500NF	400 ~ 500	0.35	20	1.25	300	300	N-F	-30 ~ +70
UIYCC4550A500T700NF	500 ~ 700	0.5	18	1.3	300	300	N-F	-30 ~ +70
UIYCC4550A690T1000SF	690 ~ 1000	0.6	18	1.3	100	100	SMA-F	-30 ~ +70
UIYCC4550A700T1000SF	700 ~ 1000	0.6	18	1.3	100	100	SMA-F	-30 ~ +70
UIYCC4550A850T1150SMTSF	850 ~ 1150	0.5	20	1.25	100	100	SMA-M to SMA-F	-30 ~ +70

² List are specify frequency range and other ranges available.

² Please enter below information when inquiry and mark * is must.


* 1. The specific frequency range

* 2. Power handling (Forward, Reverse, Peak, etc.)

* 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)

4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ± 0.2 mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com