

Keysight

## T3100S Series NFC Test Systems

Test systems for NFC, EMV and contactless device testing

### Technical Overview



The Keysight Technologies T3100S Series includes:

- T3111S NFC conformance test system
- T3121S NFC R&D test system
- T1141A NFC test set
- T1142A automatic positioning robot

The Keysight Technologies, Inc. T3100S Series NFC test systems are the essential tools for testing NFC and contactless payment devices. From chipsets to cards, terminals, and mobile devices, T3100S Series test systems cover all product development phases from R&D to pre-conformance and final certification.

Each of the T3100S Series systems is built around the Keysight T1141A NFC Test Set. Capable of supporting Analog RF and Digital Protocol testing, the T1141A combines the functions needed to test NFC devices:

- Scripted card and terminal emulation
- Arbitrary waveform generation
- Powerful waveform, logic, protocol, and voltage analysis

The Keysight T3121S NFC R&D Test System combines the T1141A with a PC hosted virtual front panel application.

The Keysight T3111S NFC Conformance Test System can be configured as a superset of the T3121S by adding a Test Manager software application, and hosting an expanding range of standards-based test suites covering:


- EMV™ Level 1 PICC/Mobile and PCD Digital Protocol
- NFC Forum Digital Protocol and Analog RF
- NFC Forum LLCP and SNEP
- ISO 14443 and 18092 NFC Digital Protocol and Analog RF
- ISO 15693 and 18000-3 RFID HF Analog RF

The T3111S Test System can be expanded with specialized EMV test accessories and software applications from FIME to cover EMV Level 1 PICC/Mobile and PCD analog RF testing.

When combined with the T3111S, the optional Keysight T1142A Automatic Positioning Robot enables accurate and repeatable antenna positioning.



The integrated T1141A NFC Test Set forms the core of the T3111S and T3121S systems.



T3100S Test System components.

## Test Manager

The Test Manager automates and controls test suite execution and report generation. The intuitive and powerful graphical user interface includes:

- Technology manager to select and load standards-based test suites
- Project manager to create, edit, save, and recall test campaigns with customized ICS, IXIT, device-under-test (DUT) information and test case selections
- Sequencer to select and execute individual tests or test campaigns
- Results analyzer to save and review test logs and statistics


Powerful utilities allow test projects to be migrated forward as test suite software is modified to support test case standards updates.

Test parameters defaults are set to support pre-conformance and conformance testing, with many parameters including additional setting flexibility.


By using the Test Manager Remote feature, users can access the T3111S system and execute test cases remotely.

## Results Analysis

Comprehensive test reports and logs allow users to review and analyze results from automated testing sessions. Captured results can also be visualized with the Virtual Front Panel software application.



Test Manager user interface



Test Manager sequencer

## Validated Test Suites

Regular software updates ensure that test suites are maintained in alignment with evolving industry standards. Keysight is a member of the NFC Forum and has been recognized by EMVCo as a test tool provider.


Many of the T3111S NFC Forum test suites have been validated by the NFC Forum with additional test suite validation underway. At the date of publishing, EMV Level 1 PICC/Mobile Digital Protocol test suite qualification is underway.

## Virtual Front Panel

Available with the T3121S and T3111S systems the Virtual Front Panel software application provides a powerful and intuitive graphical user interface for analog RF and digital protocol testing. The Virtual Front Panel can be used as an NFC device emulator or analyzer supporting NFC Forum and ISO standards. While working with the Virtual Panel, different operation modes can be selected. The analog RF Virtual Front Panel displays waveform and envelope traces captured by the T1141A test set. The digital protocol Virtual Front Panel displays logic-level traces and binary protocol decodes captured by the T1141A. In each operating mode, users are able to send message sequences to the device under test to stimulate responses for capture.


The Virtual Front Panel enables hands-on interactive testing. The tool also allows users to display waveforms, logic traces, and protocol logs saved when running automated campaigns within the Test Manager. A sniffer function allows the recording of real terminal-card protocol communication exchanges. Cursor and zooming functions enable users to perform detailed investigation of captured voltage and logic waveforms.

In addition to providing an interactive graphical user interface, the Virtual Front Panel includes a programming API enabling integration with user-developed software and systems.




R&D Virtual Panel software user interface


### Virtual Front Panel display modes:




Waveform type



Envelope type



Logical type



Protocol type

## Automatic Positioning Robot

The T1142A Automatic Positioning Robot ensures exact antenna positioning when testing NFC and EMV device RF analog performance. Robot-mounted antennas are reliably and repeatably moved under test case control to each specified position. Users can select standards-based or customized antenna measurement positions.

- Meets NFC Forum Analog RF test requirements
- Laser-assisted sample detection and location
- Positioning accuracy better than  $\pm 0.25$  mm (typical)
- Large operating volume supporting device weights up to 10 kg
- Available user calibration kit
- Non-metallic construction with three-axis, independent movement



T1142A Automatic Positioning Robot

## Worldwide Technical Support

Each T3100S system is configured with a Software and Technical Support Contract (STSC). Renewed annually, the STSC enables users to download and install regular software and firmware updates including system usability enhancements and test case standards updates.

Enhanced technical support is provided by local and factory-based NFC test experts.



# System Components

**T1141A NFC Test Set**




**Control PC <sup>1</sup>**

- Desktop PC loaded with Windows 7 (64-bit)
- Keyboard, mouse, and 19-inch widescreen LED/LCD monitor




**Keysight’s test interfaces including**

- Calibration coil
- Test coil interface (TCI)




**NFC Forum reference interfaces**

- 3 poller
- 3 listener



**ISO 10373-6 test interfaces including**

- PCD test assembly
- Calibration coil
- Reference PICC




**ISO 10373-7 test interfaces including**

- VCD antenna and sense coils
- Calibration coil
- Reference VICC



**T1142A Automatic Positioning Robot**



1. PC, operating system, and monitor details subject to change without notice. PC images courtesy of Dell Inc.

# T1141A NFC Test Set Specifications

## Technical specifications

RF generator specifications LP (TX/RX) front panel and MP rear panel BNC ports	
Frequency range	10 to 20 MHz
Nominal output impedance	50 $\Omega$
Nominal level setting resolution	< 0.04%
Typical carrier frequency accuracy	< 2 Hz from 11 to 20 MHz
LP (TX/RX) front panel	
Nominal level range	-5 to +25 dBm
Typical absolute level accuracy	$\pm 1.5$ dB from 11 to 20 MHz and -1 to 25 dBm
MP rear panel	
Nominal level range	+6 to +35 dBm
Typical absolute level accuracy	$\pm 1.5$ dB from 11 to 17 MHz and 8 to 36 dBm
Load modulator specifications LM rear panel port	
Nominal output impedance	50 $\Omega$
Nominal level range	0 to 5 V rms
RF analyzer specifications LP (TX/RX) front panel BNC port	
Frequency range	10 to 20 MHz
Nominal input impedance	50 $\Omega$
Nominal level range	0 to 20 dBm
Damage level	0 Vdc or 5 V peak
Typical absolute level accuracy	$\pm 1$ dB at 13.56 MHz and 0 to 20 dBm
RF analyzer specifications CC (RX) front panel and SC rear panel BNC ports	
Frequency range	10 to 20 MHz
Nominal input impedance	50 $\Omega$ or 1 M $\Omega$ switchable
Nominal level range	1 mV to 700 mV rms
Damage level	$\pm 2.5$ V peak
Typical absolute level accuracy	$\pm 5\%$ from 50 to 700 mV rms and 11 to 20 MHz
Typical level measurement linearity	$\pm 2\%$ from 12 to 700 mV rms and 13.56 MHz
Nominal residual reading for 0V input	< 3.5 mV rms
Nominal freq. measurement accuracy	< 10 Hz
DC voltmeter	
Nominal input impedance	> 10 M $\Omega$
Nominal level range	0 to 10 Vdc
Damage level	12 Vdc
Typical absolute level accuracy	$\pm 1.59\%$ from 0 to 10 Vdc

# T1141A NFC Test Set Specifications (continued)

## Technical specifications (continued)

Nominal performance with Keysight antennas	
ISO 10373-6 test assemblies	Nominal output field range: 0.1 to 2 A/m with LP (TX/RX) front panel output 0.25 to 7.75 A/m with MP rear panel output Nominal output field resolution: 0.02 A/m with LP (TX/RX) front panel output 0.06 A/m with MP rear panel output
Keysight test coil interface	Nominal output field range: 0.5 to 3 A/m with LP (TX/RX) front panel output Nominal output field resolution: 0.05 A/m with LP (TX/RX) front panel output

Output and reception uncertainties	
	Compliant to NFC Forum requirements for test tools <sup>1</sup>

## Processing parameters

Maximum sampling rate	108.48 Msps
ADC resolution	14 bits
DAC resolution	16 bits

## Signaling parameters

Standards supported	EMVCo Level 1 NFC Forum Digital Protocol NFC Forum Analog RF NFC Forum LLCP NFC Forum SNEP	ISO/IEC 14443 (Type A and Type B) ISO/IEC 18092 ISO/IEC 15693 ISO/IEC 18000-3 (Mode 1)
Modulation supported	ASK Load modulation BPSK	
Modulation index	ASK 1 to 100% (adjustable)	
Bit rate	106 to 848 kbps	

## General specifications

Dimensions (W x H x D)	456 x 155 x 363 mm
Weight	8.6 Kg

## Environmental and safety

Supply voltage range	100 to 120 VAC and 200 to 240 VAC
Supply frequency range	50 Hz (220 V range) and 60 Hz (110 V range)
Operating temperature	10 to 35° C
Storage temperature	-20 to +60° C
Humidity	20 to 80%
Calibration	1 year



T1141A NFC Test Set (front and rear panels)

1. Uncertainties requirements defined at NFC Analog RF Test Specifications.



# T1142A Automatic Positioning Robot Specifications

## General specifications

Control interfaces	
Serial	1 x USB connection
Power supply	
External power supply	24 V 100 to 240 V, 50 to 60 Hz
Power consumption	80 W
Dimensions (W x H x D)	1100 x 800 x 800 mm
Storage ranges	
Temperature	-20 to 80 °C
Humidity	20 to 90% non condensing
Operation ranges	
Temperature	15 to 30 °C
Humidity	20 to 90% non condensing
EMC	IEC-61326
Electrical safety	IEC 61010-1
Recommended calibration interval	1 year

## Performance features

Speed	
X axis	44 mm/s
Y axis	19 mm/s
Z axis	19 mm/s
Threads per mm	
X axis	32
Y axis	32
Z axis	800
Precision (positioning within the NFC Forum defined test volume)	±0.26 mm; <i>±0.15 mm typical</i>
Effective operation volume (W x H x D)	350 x 320 x 320 mm
Free guard area <sup>1</sup>	> 150 mm
Maximum DUT dimensions allowed	645 x 320 x 645 mm
Maximum DUT weight allowed	10 kg
Warm up time	N/A

1. Distance from reference antenna to any disturbing elements.

## Ordering Information

Following tables described options for available products

- T3111S NFC Conformance Test System is the Keysight platform for NFC and RFID HF conformance testing of contactless devices.
- T3121S NFC R&D Test System is the Keysight platform for NFC and RFID HF R&D testing of contactless devices.
- T1142A Automatic Positioning Robot

### T3111S hardware options

Option	Description
T3111S-H01	NFC test set, PC, and Test Manager 2.0 license

### T3111S test antennas

Option	Description
T3111S-SH1	ISO 10373-6 test assemblies
T3111S-RH1	ISO 10373-7 test assemblies
T3111S-CH1	NFC Forum reference test assemblies
T3111S-CH2 <sup>1</sup>	Test coil set includes test coil interface and calibration coil

### T3111S software options

#### NFC Forum conformance test cases packages

Option	Description
T3111S-C01	NFC Forum Analog RF test suite
T3111S-C02	NFC Forum Digital Protocol test suite
T3111S-C03	NFC Forum LLCP test suite
T3111S-C04	NFC Forum SNEP test suite

#### EMV™ Level 1 test suites

Option	Description
T3111S-V01	EMV PICC and Mobile L1 Digital Protocol test suite
T3111S-V02	EMV PCD L1 Digital Protocol test suite

#### ISO NFC conformance test cases packages

Option	Description
T3111S-S01	ISO Analog RF test suites (ISO 14443 and 18092)
T3111S-S02	ISO Digital Protocol test suites (ISO 14443 and 18092)

#### ISO RFID HF conformance test cases packages

Option	Description
T3111S-R01	RFID HF Analog RF test suites (ISO 15693 and 18000-3)

#### R/D software options

Option	Description
T3111S-D01	Analog RF Virtual Front Panel (NFC, ISO, and RFID HF)
T3111S-D02	Digital Protocol Virtual Front Panel (NFC, ISO, and RFID HF)

1. T3111S-CH2 is the recommended test interface for NFC Forum Digital Protocol, LLCP, and SNEP. It is also recommended for the T3121S Test System.

## Ordering Information

### T3111S software options (continued)

#### Calibration

Option	Description
T3111S-1AC	Accredited calibration certificate

### T3111S support options

Option	Description
T3100SC	NFC test system support

### T3121 hardware options

Option	Description
T3121S-H01	NFC test set and virtual panel R/D software platform

### T3121 software options

#### NFC R/D options

Option	Description
T3121S-D01	NFC R/D RF tester
T3121S-D02	NFC R/D protocol analyzer

#### ISO RFID HF R/D options

Option	Description
T3121S-D41	ISO RFID HF R/D RF tester
T3121S-D42	ISO RFID HF R/D protocol analyzer

#### NFC/ISO RFID HF protocol sniffer

Option	Description
T3121S-D81	NFC/ISO RFID HF protocol sniffer

### T1142A options

Option	Description
T1142A-F01	Automatic Positioning Robot with fixed head and three axis of movement
T1142A-C01	Calibration kit for T1142A
T1142A-C02	Holder kit for EMV test equipment

**myKeysight****myKeysight**[www.keysight.com/find/mykeysight](http://www.keysight.com/find/mykeysight)

A personalized view into the information most relevant to you.

**Three-Year Warranty**[www.keysight.com/find/ThreeYearWarranty](http://www.keysight.com/find/ThreeYearWarranty)

Keysight's commitment to superior product quality and lower total cost of ownership. The only test and measurement company with three-year warranty standard on all instruments, worldwide.

**Keysight Assurance Plans**[www.keysight.com/find/AssurancePlans](http://www.keysight.com/find/AssurancePlans)

Up to five years of protection and no budgetary surprises to ensure your instruments are operating to specification so you can rely on accurate measurements.

[www.keysight.com/go/quality](http://www.keysight.com/go/quality)

Keysight Technologies, Inc.

DEKRA Certified ISO 9001:2008

Quality Management System

**Other Keysight Test Systems**

Keysight test systems portfolio offers a broad range of wireless technologies testing solutions, including:

- Bluetooth®
- LTE
- UMTS
- GSM, GPRS, EDGE

Bluetooth and Bluetooth logos are trademarks owned by Bluetooth SIG, Inc., USA and licensed to Keysight Technologies, Inc..

EMV is a trademark owned by EMVCo LLC.

[www.keysight.com/find/systems](http://www.keysight.com/find/systems)

For more information on Keysight Technologies' products, applications or services, please contact your local Keysight office. The complete list is available at: [www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)

**Americas**

Canada	(877) 894 4414
Brazil	55 11 3351 7010
Mexico	001 800 254 2440
United States	(800) 829 4444

**Asia Pacific**

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 6375 8100

**Europe & Middle East**

Austria	0800 001122
Belgium	0800 58580
Finland	0800 523252
France	0805 980333
Germany	0800 6270999
Ireland	1800 832700
Israel	1 809 343051
Italy	800 599100
Luxembourg	+32 800 58580
Netherlands	0800 0233200
Russia	8800 5009286
Spain	800 000154
Sweden	0200 882255
Switzerland	0800 805353
	Opt. 1 (DE)
	Opt. 2 (FR)
	Opt. 3 (IT)
United Kingdom	0800 0260637

For other unlisted countries:  
[www.keysight.com/find/contactus](http://www.keysight.com/find/contactus)  
 (BP-09-23-14)