




产品型号 type	配接电缆 cable type
DSB-JWB3	SFT-50-3-1-RG402/U

Electrical Characteristics:

1. Characteristic Impedance: $50\ \Omega$
2. Frequency range: DC~2Ghz
3. Contact resistance
Center conductor: $\leq 6.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
4. Insulation resistance: $\geq 10000M\Omega$
5. Insulator withstanding: 750V
6. Durability: 500cycles

Application: DIN 41626

Material&Finishing

1. Center contact :
Male: beryllium copper, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE

主要性能指标:

1. 特性阻抗: $50\ \Omega$
2. 频率范围: DC~2Ghz
3. 接触电阻:
中心导体: $\leq 6.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
4. 绝缘电阻: $\geq 10000M\Omega$
5. 介质耐压: 750V
6. 插拔次数: 500次

执行标准: DIN 41626

材料和镀层

1. 中心接触件:
插针: 铍青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

				SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
				2.5:1		
		NAME		DATE		DSB-JWB3 RF COAXIAL CONNECTOR 西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.
DRAWN						
CHECKED						
APPROVED						