LOW PROFILE ANTENNA LPA7-900V-503/770



ELECTRICAL		SIDE			
FREQUENCY:	870 - 960 MHz	VIEW	224.20[8.83]		
GAIN:	8 dBi			A	
POLARISATION:	Linear (Vertical)	#			
BEAMWIDTH:	70° (Az) x 60° (EI)				
CROSS POLAR:	20 dBTyp.				
VSWR:	2:1				
POWER RATING:	50 W			11.8	
FRONT TO BACK:	20 dBTyp.]		300 [11.81]	
		20		30	
MECHANICAL		165 [6.50]			
STANDARD FINISH:	ABS Polymer - White				•
MASS:	0.75 kg / 1.65 lbs				ISOMETRIC
TEMPERATURE:	–20° to +50°C		/\/\` 		VIEW
WIND LOADING:	11.97 kg / 26.3 lbs @ 100 mph	40[1.57		ϕ 5.5 [0.22] HOLES	
			N(M) CONNEC & INTEGRAL 50		
MOUNTING OF	PTIONS	4		00mm CABLE	
KITS AVAILABLE:	N/A				
See Separate Data	Sheets			0.79	
			L		
				50	
			246[9.69]	I	
GA: 770-1	lssued: 280308				
DIMENSIONS: mm	[inches]	VIEW			

European Antennas Ltd. has a policy of continuous development and therefore stress that the data contained on this sheet should be used for guidance only.

European Antennas Ltd. is part of the Cobham Antennas Division





Certificate No 9268

European Antennas Ltd Lambda House, Cheveley Newmarket, Suffolk, CB8 9RG, UK Tel: +44 (0)1638 731888 sales@european-antennas.co.uk www.european-antennas.co.uk