


NO.	COMPONENTS	IMPEDANCE
1	SMA MALE RIGHT ANGLE	50 OHM
2	.085" HANDBENDABLE CABLE (= JYEBAO P/N .085SRF-W-P-50)	50 OHM
3	SMA FEMALE FOR BULKHEAD	50 OHM

SMA MALE
RIGHT ANGLE



2




L

SMA FEMALE
FOR BULKHEAD

3

GASKET




1/4-36UNS-2A

0.8 [0.315] HEX

1.1 [0.433] HEX

0.575
[0.226]

JYE BAO P/N	L CM (INCH)
A39A85-85S-15	15 (5.906)
A39A85-85S-30	30 (11.811)
A39A85-85S-50	50 (19.685)
A39A85-85S-100	100 (39.370)
A39A85-85S-150	150 (59.055)
A39A85-85S-200	200 (78.740)
A39A85-85S-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 10\text{MM}$, WHICHEVER IS GREATER.	JYE BAO CO., LTD. TAIPEI TAIWAN	
	DESCRIPTION	CABLE ASSEMBLY SMA PLUG R/A TO SMA JACK FOR BULKHEAD
	JYE BAO DRAWING NO.	A39A85-85S-XXX