

AMP5006

SOLID STATE HIGH POWER AMPLIFIER

PRELIMINARY



FEATURES

- Class AB linear LDMOS design
- Instantaneous wide bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	5.712 GHz	
Power Output Psat	500 Watt Min	CW
Power Gain	56 dB Min	
Input Return Loss	10 dB Min	Relative to 50 Ohm
Harmonics	>30 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc	
Operating Voltage	48 VDC	
Current Consumption	35 Amp Typ	At rated Pout
Max Input Power	8 dBm	Without damage
Load VSWR Protection	5 : 1	Connect load at all times

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	500 x 400 x 60mm – or – 350 x 250 x 200mm	Excluding Connectors
Weight	TBD g.	Typical Weight
RF Connectors In/Out	SMA F / N-Type F	
DC Power / Interface Connector	Hybrid D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	N/C
2	REV	N/C
3	CURRENT MONITOR	$I_D @ 10mV/100mA$ Typ
4	TEMP SENSOR	$V_T @ 10mV/°C + 500mV$ Typ
5	SHUTDOWN	TTL
A1	VDD	48VDC
A2	GND	Ground



AMP5006
SOLID STATE HIGH POWER AMPLIFIER
PRELIMINARY

OUTLINE DRAWING