

130 to 180MHz 500W – Drop in Circulator

Design Features

- ◆ Can be dual junction even three for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Guaranteed for one year standard.

RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYDC6466B130T136	130 ~ 136	0.5	20	1.25	500	500	TAB	-20 ~ +65
UIYDC6466B135T140	135 ~ 140	0.5	20	1.25	500	500	TAB	-20 ~ +65
UIYDC6466B144T148	144 ~ 148	0.5	20	1.25	500	500	TAB	-20 ~ +65
UIYDC6466B150T170	150 ~ 170	0.7	18	1.3	500	500	TAB	-20 ~ +65
UIYDC6466B164T170	164 ~ 170	0.5	20	1.25	500	500	TAB	-20 ~ +65
UIYDI6466B1625	162.5	0.35	23	1.15	500	500	TAB	-20 ~ +65
UIYDC6466B170T180	170 ~ 180	0.6	20	1.25	500	500	TAB	-20 ~ +65

² List are specify frequency range and other ranges available.


² Please enter below information when inquiry and mark * is must.

* 1. The specific frequency range

* 2. Power handling (Forward, Reverse, Peak, etc.)

* 3. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ± 0.2 mm unless otherwise stated.

Ver. 5

A2-5G, Zhujiang Plaza, Longxiang Blvd, Longgang District, Shenzhen 518172, China.

Tel: +86-755-25999990 25999909 Fax: +86-755-25999959 E-mail: sales@uiy.com Web: www.uiy.com