

GaAs SP3T / SPDT DC - 6.0 GHz (Optimized for 2.4 / 5.8 GHz operation)

Rev. V2

Features

- Dual Band, Integrated SP3T (2.4 GHz) and SPDT (5.8 GHz) Switch
- Ideal for 802.11n, ac Applications
- Lead-Free 2 mm 12-Lead STQFN package
- Halogen-Free “Green” Mold Compound
- RoHS* Compliant and 260°C Reflow Compatible


Description

The MASW-011043 is an integrated MMIC design which includes a SPDT switch and a SP3T switch. This part would typically be used on the front end of 802.11 n, ac applications.

This switch delivers high isolation and low insertion loss in a lead free 2 mm 12-lead STQFN package.

The MASW-011043 is ideal for broad band applications. The low frequency roll-off is controlled by the series blocking capacitors.

Functional Schematic



Pin Configuration^{3,4}

Pin No.	Function	Description
1	V_Rx5	Vcontrol SP2T R _x
2	V_Tx5	Vcontrol SP2T T _x
3	R _x 5	SPDT R _x Port
4	T _x 5	SPDT T _x Port
5	V_Tx2	Vcontrol SP3T T _x
6	T _x 2	SP3T T _x Port
7	R _x 2	SP3T R _x Port
8	BT2	SP3T BT Port
9	V_Rx2	Vcontrol SP3T R _x
10	RFC2	SP3T RFC Port
11	V_BT2	Vcontrol SP3T BT
12	RFC5	SP2T RFC
13	GND (paddle)	Ground

3. The exposed pad centered on the package bottom must be connected to RF, DC and thermal ground.
4. To achieve optimum performance, connect 620 Ω, size 0201 resistors to all control pins. See recommended PCB layout on page 6.

Ordering Information^{1,2}

Part Number	Package
MASW-011043-TR3000	3000 piece reel
MASW-011043-001SMB	Sample Board

1. Reference Application Note M513 for reel size information.
2. All sample boards include 5 loose parts.

* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.

GaAs SP3T / SPDT DC - 6.0 GHz (Optimized for 2.4 / 5.8 GHz operation)

Rev. V2

SP3T Electrical Specifications:

Freq. = 2.4 GHz, $T_A = 25^\circ\text{C}$, $V_{\text{Control}} = 0\text{ V} / 3\text{ V}$, $P_{\text{IN}} = 0\text{ dBm}$, $Z_0 = 50\ \Omega^5$

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Insertion Loss	RFC2 to $T_{X2}/R_{X2}/BT2$	dB	—	0.6	0.9
Isolation	RFC2 to T_{X2}	dB	22	27	—
	RFC2 to R_{X2}		25	30	
	RFC2 to BT2		25	30	
	$R_{X2}-T_{X2}$ (T_{X2} IL)		—	27	
	T_{X5} to R_{X2} (R_{X2} IL)		—	33	
Return Loss	—	dB	—	25	—
Input P0.1dB	3 V	dBm	—	26	—
	5 V			32	
Input P1dB	3 V	dBm	—	29	—
	5 V			35	
Output IP3	1 MHz Spacing, 15 dBm, 3 V	dBm	—	54	—
	1 MHz Spacing, 15 dBm, 5 V			57	
2nd Harmonic	T_{X2} , 20 dBm, 3 V	dBc	—	-68	—
	T_{X2} , 20 dBm, 5 V			-71	
T_{ON} , T_{OFF}	50% control to 90% RF 50% control to 10% RF	ns	—	200	—
Current	$V_{\text{Control}} = 3\text{ V}$	μA	—	1.5	5.0

5. External DC blocking capacitors are required on all RF ports. Specified performance is with 22 pF capacitors as shown in the recommended PCB layout on page 6.

GaAs SP3T / SPDT DC - 6.0 GHz (Optimized for 2.4 / 5.8 GHz operation)

Rev. V2

SPDT Electrical Specifications:

Freq. = 5.8 GHz, $T_A = 25^\circ\text{C}$, $V_{\text{Control}} = 0\text{ V} / 3\text{ V}$, $P_{\text{IN}} = 0\text{ dBm}$, $Z_0 = 50\ \Omega$ ⁶

Parameter	Test Conditions	Units	Min.	Typ.	Max.
Insertion Loss	RFC5 to T _{X5} /R _{X5}	dB	—	0.95	1.25
Isolation	RFC5 to T _{X5} RFC5 to R _{X5} R _{X5} to T _{X5} R _{X5} to T _{X2}	dB	16 16 — —	21 21 21 30	—
Return Loss	—	dB	—	17	—
Input P0.1dB	3 V 5 V	dBm	—	26 29	—
Input P1dB	3 V 5 V	dBm	—	32 35	—
Output IP3	1 MHz Spacing, 15 dBm, 3 V 1 MHz Spacing, 15 dBm, 5 V	dBm	—	52 56	—
2nd Harmonic	T _{X5} , 20 dBm, 3 V	dBc	—	-70	—
2nd Harmonic Interferer	Rx5: Stimulate Tx2, 20 dBm, 3 V	dBc	—	-50	—
T _{ON} , T _{OFF}	50% control to 90% RF 50% control to 10% RF	ns	—	14	—
Current	$V_{\text{Control}} = 3\text{ V}$	μA	—	1.5	5.0

6. External DC blocking capacitors are required on all RF ports. Specified performance is with 8 pF capacitors as shown in the recommended PCB layout on page 6.


GaAs SP3T / SPDT

DC - 6.0 GHz (Optimized for 2.4 / 5.8 GHz operation)


Rev. V2

SP3T Typical Performance Curves:


Insertion Loss




Isolation RFC2 - RX2




Input Return Loss (Insertion Loss Cases)




Isolation RFC2 - TX2



Output Return Loss (Insertion Loss Cases)



Isolation RFC2 - BT2




GaAs SP3T / SPDT DC - 6.0 GHz (Optimized for 2.4 / 5.8 GHz operation)


Rev. V2

SPDT Typical Performance Curves:


Insertion Loss




Isolation



Return Loss (Insertion Loss Cases)



Return Loss (Isolation Cases)




Rev. V2

Parameter	Absolute Maximum
Input Power (0.5 - 6.0 GHz, 3 V Control)	+32.0 dBm SPDT +33.5 dBm SP3T
Control Voltage	+5 volts
Operating Temperature	-40°C to +85°C
Storage Temperature	-65°C to +150°C

- | State | V_BT2 | V_Rx2 | V_Tx2 | V_Rx5 | V_Tx5 | Insertion Path | Band |
|-------|-------|-------|-------|-------|-------|----------------|---------|
| 1 | 1 | 0 | 0 | 0 | 0 | RFC2 - BT2 | 2.4 GHz |
| 2 | 0 | 1 | 0 | 0 | 0 | RFC2 - Rx2 | 2.4 GHz |
| 3 | 0 | 0 | 1 | 0 | 0 | RFC2 - Tx2 | 2.4 GHz |
| 4 | 0 | 0 | 0 | 1 | 0 | RFC5 - Rx5 | 5.8 GHz |
| 5 | 0 | 0 | 0 | 0 | 1 | RFC5 - Tx5 | 5.8 GHz |

- For further information and support please visit:
<https://www.macom.com/support>

Recommended PCB Layout^{12,13}



12. The exposed pad centered on the package bottom must be connected to ground to ensure a good thermal path.

13. To achieve optimum performance, connect 620 Ω , size 0201 resistors to all control pins.

Parts List

Component	Value	Package
C1 - C3	8 pF	0201
C4 - C7	22 pF	0201
R1 - R5	620 Ω	0201

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.