

REVISIONS			
DATE	REV	DESCRIPTION	APPROVED
8/7/09	1	ORIGINAL RELEASE	

Description:

Low Noise Amplifier designed for Military and Industrial applications. This amplifier is supplied in our standard PE2 housing that can be used as a SMA connectorized or a surface mount component. Other packages and connector types are available.

This model provides the following performance. Data is available upon request.

Specifications:

Frequency Range: 1.0 to 6.0 GHz
Gain: 45dB Typ.
Gain Flatness: +/-1.25dB Max.
Noise Figure: 4.5dB Typ.
OP1dB: 20dBm Min.
VSWR Input/Output: 2.0:1 Max.
DC Voltage Supply: +12 to +15VDC
DC Current Draw: 385mA Max.

Features:

Internal Voltage Regulation
Unconditional Stability
Standard Operating Temperature -20 to +70 Deg. C

Available Options:

Various Package types
Various Connector types
Temperature Compensation
Hermetic Sealing
Gain and Phase Matching
MIL-STD-883 Screening Available

Environmental Ratings:

Temperature: -20 to +70 Deg. C (Operating) ; -55 to +85 Deg C (Available)

Humidity: MIL-STD-202F, METHOD 103B COND B.


Shock: MIL-STD-202F, METHOD 213B COND B.

Altitude: MIL-STD-202F, METHOD 105C COND B.


Temperature Cycle: MIL-STD-202F, METHOD 107D COND A

Note: The above specifications are subject to change or revision.

PE2 HOUSING WITH CARRIER



PE2 HOUSING WITHOUT CARRIER (SURFACE MOUNT)



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
± ± ±
.XXX ± 0.005

PART NO.		DATE		TITLE	
MATERIAL:		FINISH:		DO NOT SCALE DRAWING	
6061-T6 Aluminum		Gold Plate over Nickel			
K. Mason		2/21/09		PE2-45-1806R0-4R5-22-12-SFF	
B. 1LK53		WEB - MODEL		A	