



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)577-9887  
 WEB: [www.ophirrf.com](http://www.ophirrf.com) • E-MAIL: [sales@ophirrf.com](mailto:sales@ophirrf.com)

## MODEL 5803052

20 - 1000 MHz  
 1.0 WATTS

### Solid State Broadband High Power RF Amplifier

The 5803052 is a 1.0 Watt broadband amplifier that covers the 20 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5803052 comes with an extended

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	20 – 1000 MHz
2	Saturated Output Power	1.0 Watts typical
3	Power Output @ 1dB Comp.	0.6 Watts min
4	Small Signal Gain	+30 dB min
5	Gain Flatness	± 1.0 dB max
6	IP <sub>3</sub>	+35 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 0.6 Watt
9	Spurious Signals	> -60 dBc typical @ 0.6 Watt
10	Input/Output Impedance	50 Ohms nominal
11	DC Input Current	1.0 Amp max
12	DC Input	28 VDC nominal
13	RF Input	0 dBm
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<b>Mechanical</b>		
16	Dimensions (w/heatsink)	6.3" x 4.4" x 2.2"
17	Weight (w/heatsink)	2.5 lb. max
18	Connectors	SMA female
19	Grounding	Chassis
20	Cooling	Adequate Airflow Required
<b>Environmental</b>		
21	Baseplate Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



### FEATURES:

Heatsink and Fans Included (Not Shown)