



## WR-430 to N Female Waveguide to Coax Adapter 1.7 GHz to 2.6 GHz

### **TECHNICAL DATA SHEET**

PE9872

#### WR-430 to N Female Waveguide to Coax Adapter 1.7 GHz to 2.6 GHz

Configuration

Waveguide Interface WR-430
RF Connector N Female
RF Connector Impedance 50 Ohms

**Electrical Specifications** 

Frequency Range, GHz 1.7 to 2.6 Maximum VSWR 1.3:1

#### **Mechanical Specifications**

Size

 Length, in [mm]
 3.5 [88.9]

 Width/Dia., in [mm]
 6.34 [161.04]

 Height, in [mm]
 4.36 [110.74]

**Waveguide Interface** 

Type WR-430
Body Material and Plating Aluminum

**RF Connector** 

Type N Female

Body Material and Plating Passivated Stainless Steel

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

WR-430 to N Female Waveguide to Coax Adapter 1.7 GHz to 2.6 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: WR-430 to N Female Waveguide to Coax Adapter 1.7 GHz to 2.6 GHz PE9872

URL: http://www.pasternack.com/wr-42-sma-female-waveguide-coax-adapter-18-26.5-ghz-pe9872-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE9872 CAD Drawing

WR-430 to N Female Waveguide to Coax Adapter 1.7 GHz to 2.6 GHz

