





剥线尺寸
stripping dimensions



产品型号 type	L	D	A	B	电缆型号 cable type
SMB-JW2	13.7	Ø0.9	10.0	3.5	SFF-50-1-RG178/U
SMB-JW3	15.1	Ø1.6	11.0	5.0	SFF-50-1.5-1-RG316/U

Electrical Characteristics:

1. Characteristic Impedance: 50 Ω
2. Frequency range: DC~3Ghz
3. Contact resistance
Center conductor: ≤6.0 mΩ
Out conductor: ≤1.0 mΩ
4. Insulation resistance: ≥1000MΩ
5. Insulator withstanding: 750V
6. VSWR: ≤1.4
7. Durability: 500cycles

Application: MIL-C-39012/68A

Material&Finishing

1. Center contact:
male: phosphor bronze, gold plated
2. Body: brass, gold plated
3. Crimp ferrule: copper, nickel plated
4. Insulators: PTFE


主要性能指标:

1. 特性阻抗: 50 Ω
2. 频率范围: DC~3Ghz
3. 接触电阻:
中心导体: ≤6.0 mΩ
外导体: ≤1.0 mΩ
4. 绝缘电阻: ≥1000MΩ
5. 介质耐压: 750V
6. 电压驻波比: ≤1.4
7. 插拔次数: 500次

执行标准: MIL-C-39012/68A

材料和镀层

1. 中心接触件:
插针: 锡磷青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 线夹: 黄铜, 镀镍
4. 绝缘子: 聚四氟乙烯

		SCALE		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±	
		2.5:1			
		NAME	DATE		SMB-JW2 RF COAXIAL CONNECTOR
DRAWN					
CHECKED					
APPROVED				西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.	