



Model: SR-S000-5S

Description:..... SP5T, Reflective, PIN-Switch

Operating Frequency:..... 2 – 18 GHz

Insertion Loss:

2 – 10 GHz	10 – 18 GHz
2.2 dB Max	2.8 dB Max

Isolation:

2 – 10 GHz	10 – 18 GHz
80 dB Min	70 dB Min

VSWR (“ON” paths):..... 1.8:1 Max

Rise/Fall time (10% to 90% RF, 90% to 10% RF): ... 10 ns Max

On/Off time (50% TTL to 90% RF, 50%TTL to 10% RF):..... 50 ns Max

Operating Power:..... CW&AVG..... +30dBm Max

..... Peak: 10W @ 1μS PW Max

Control Input Characteristics: TTL /Unit-Load / Floating-High

Control Logic:..... 5-Controls, Logic “0” = RF Path “ON”

Power Supplies:..... +5(±0.25)V @ 160mA Max

..... -12(±0.5)V @ 80mA Max

Connectors (RF): SMA (f), Removable

Connectors (Supplies/Controls) Solder Pins

Impedance: 50 Ohms Nominal

Quality:..... Best-Commercial-Grade

Environmental Ratings:

Temperature:..... {Operating: -55°C to +95°C} & {Storage: -60°C to +110°C}

Humidity: MIL-STD-202F, Method 103B, Cond. B (96 hours at 95% R.H.)

Shock: MIL-STD-202F, Method 213B, Cond. B (75G, 6mSec)

Vibration: MIL-STD-202F, Method 204D, Cond. B (.06” double amplitude, or 15G)

Altitude: MIL-STD-202F, Method 105C, Cond. B (50,000 Feet)

Temp. Shock: MIL-STD-202F, Method 107D, Cond. A (5 cycles)

Available Options:

(Units with listed options here may be subject to some specification tradeoffs from the standard, consult factory)

■ **Supply Voltages**

A1 [+5(±0.25)V / -5(±0.25)V]

A2 [+5(±0.25)V / -15(±0.5)V]

A3 [+12(±0.5)V / -12(±0.5)V]

A4 [+15(±0.5)V / -15(±0.5)V]

■ **RF Connectors**

B1 [J1 – J5 Ports with SMA(M)]

B2 [All SMA (M)]

B3 [COM Port with SMA(M)]

■ **Control Function**

F1 [Inverse Logic, (“1” = Path “ON”)]

F2 [3-BCD Controls]

■ **Video Suppression Filter**

G1 [VF @ COM Port <> 0.25 dB additional Loss]


G2 [VF @ J1 – J5 Ports <> 0.25 dB additional Loss]

G3 [VF @ All Ports <> 0.5 dB additional Loss]



Model: SR-S000-5S

Outline



Weight	Tolerances
1.6 oz [45.4g]	±0.015" [±0.38mm]