

DESCRIPTION:

PMI MODEL NUMBER DTA-2G18G-60-CD-1 IS A NON-REFLECTIVE 10 BIT PROGRAMMABLE 60 DB PIN DIODE ATTENUATOR WITH STEP RESOLUTION AS LOW AS 0.06 DB OVER THE FREQUENCY RANGE OF 2.0 TO 18.0 GHZ.

SPECIFICATIONS:


- FREQUENCY: 2 GHZ TO 18.0 GHZ
- MEAN ATTENUATION RANGE: 60dB
- INSERTION LOSS: 4.5 dB MAX
- VSWR: 2.0 :1 MAX
- FLATNESS UP TO
 - 20 dB ±1.0 dB TYP
 - 40 dB ±1.25 dB TYP
 - 60 dB ±3.0 dB TYP
- ACCURACY OF ATTENUATION
 - 0 dB TO 20 dB ±1.0 dB TYP
 - 20 dB TO 40 dB ±1.5 dB TYP
 - 40 dB TO 60 dB ±2.0 dB TYP
- MINIMUM ATTENUATION STEP: 0.06 dB
- SURVIVAL POWER: 2W Average from -65C to +25C
- SWITCHING TIME
 - ON TIME 1.0 USEC MAX
 - OFF TIME 0.5 USEC MAX
- DC POWER SUPPLY: +15V @ 100mA MAX
-15V @ 100 mA MAX
- CONNECTORS: 2 SMA & 15 PIN D-SUB
Shipped with Mating D-SUB
- WEIGHT: 3.0 oz (85 gm) Approximate
- FINISH: PAINTED GREY
- LOGIC INPUT
 - LOGIC "0" (BIT OFF) -0.3 to +0.8V
 - LOGIC "1" (BIT ON) +2.0 to +5.0V

ENVIRONMENTAL RATINGS:



- TEMPERATURE: -50°C TO +100°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107

NOTE: THE ABOVE SPECIFICATIONS ARE SUBJECT TO CHANGE OR REVISION

PIN NO:	J3 PIN FUNCTIONS
1	GND
2	Not Connected
3	0.13 dB
4	GND
5	0.25 dB
6	0.5 dB
7	1.0 dB
8	2.0 dB
9	4.0 dB
10	8.0 dB
11	16.0 dB
12	32.0 dB (MSB)
13	+V
14	-V
15	0.06 dB (LSB)



REVISIONS			
ZONE	REV.	DESCRIPTION	DATE
	A	ORIGINAL RELEASE	2/9/11



SMA(F) – (2 PLACES)

PLANAR MONOLITHICS INDUSTRIES, INC.

7311-F GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-5019 FAX: 301-662-1731
WEBSITE: www.pmi-irf.com
E-MAIL: sales@pmi-irf.com
ISO 9001:2008 CERTIFIED



TITLE		PRODUCT FEATURE		
APPROVALS	DATE	DTA-2G18G-60-CD-1		
DRAWN	2/9/11	SIZE	FSCM NO.	DWG NO.
CHECKED		A	05X00	27013141
ISSUED		SCALE	N:S	SHEET 1 OF 1