

## SMA Female Connector Crimp/Solder Attachment For RG316, RG174, RG188



## TECHNICAL DATA SHEET

PE4414

## SMA Female Connector Crimp/Solder Attachment For RG316, RG174, RG188

Configuration

Connector SMA Female Connector Specification MIL-STD-348

Connector Interface Type RG316,RG174,RG188

Cable Attachment Method (Shield/Contact)

Crimp/Solder

Body Style

Straight

**Electrical Specifications** 

Frequency Range, GHz DC to 18 Impedance, Ohms 50 Dielectric Withstanding Voltage, Vrms 750

**Mechanical Specifications** 

**Temperature** 

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 0.81 [20.57]

 Width/Dia., in [mm]
 0.312 [8]

 Weight, lbs [g]
 0.008 [3.63]

Connector

Type SMA Female

Mating Cycles 100

Contact Material and Plating Beryllium Copper, Gold

Body Material and Plating Brass, Nickel Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

**Plotted and Other Data** 

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-standard-rg316-rg174-rg188-connector-pe4414-p.aspx

SMA Female Connector Crimp/Solder Attachment For RG316, RG174, RG188 from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



