Adapters, Between-Series

Quick Connect 7/16 to Type N, DC - 7.5 GHz

SPECIFICATIONS:

Models: 5706Q; 5707Q

RoHS Compliant

AEROFLEX
A passion for performance.

Electrical:

Frequency Range	DC - 7.5 GHz
VSWR:	
DC To 2GHz	1.20:1 Maximum
2 To 7.5GHz	1.35:1 Maximum
Impedance	50 Ohms
Operating Temp Range	-65°C to +85°C
* Typical PIM	5707Q <-165 dBc
	5706Q <-155 dBc

Mechanical:

Connectors (Mates with MIL-STD-348)	White Bronze Plated Brass
Conductors	Gold Plated Beryllium Copper
Coupling Nuts	
7/16 Male	White Bronze Plated Brass
Type N Male	Passivated Stainless Steel

* Swept Data over 1930 - 1990 MHz, 2x20 W Tones



Model Number: 5706Q

DIN-7/16 Male To Type N Female



Model Number: 5707Q

DIN-7/16 Male To Type N Male



Note: Dimensions in Brackets are Expressed in Millimeters and are for Reference Only.
Design, specifications are subject to change without notice. Contact factory for technical specifications before purchasing or use.

5706Q: REV C

AEROFLEX INMET

Aeroflex / Inmet, Inc. • 300 Dino Drive, Ann Arbor, MI 48103 • U.S.A.
888-244-6638 or 734-426-5553 • FAX: 734-426-5557
www.aeroflex.com/inmet • inmetsales@aeroflex-.com