


REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS

Frequency Range: 0.8–2.3 GHz
 VSWR: 1.25:1 Max.
 Coupling: 10 ± 1.25 dB
 Insertion Loss: 1.0 dB Max.
 Directivity: 20 dB Min.
 Frequency Sensitivity: ± 0.5 dB
 Power Incident, Reflected: 50W, 5W, 1kW Peak

MATERIAL:		MCLI MICROWAVE COMMUNICATIONS LABORATORIES INC. 7255 30TH AVE. N. SAINT PETERSBURG, FL 33710 TEL: (727) 344-6254 FAX: (727) 381-6116 http://WWW.MCLI.COM		SCALE: N/A
		UNLESS OTHERWISE SPECIFIED: TOLERANCES IN (INCHES) OR [mm] (MILLIMETERS) FRACTIONS: $\pm 1/64$ DECIMALS: $\pm 0.01 \pm 0.05$ ANGLE: $\pm 1/2^\circ$		SHEET: N/A
DRAWN: Paiboon Luekhamhan		DATE: 10-01-1999		DRAWING TITLE: DIRECTIONAL COUPLER
APPROVED: T. Nguyen		DATE: 10-01-1999		
PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)		PART NO. C37-10		
THIRD ANGLE PROJECTION 		CAGE CODE: OD2L5	SIZE: A REV: B DO NOT SCALE THE DRAWING	DWG NO. 81417