


DESCRIPTION

This class AB GaN module is designed for both military and commercial applications. It is capable of supporting any signal type and modulation format, including but not limited to 3-4G telecom, WLAN, OFDM, DVB, and CW/AM/FM. The latest device technologies and design methods are employed to offer high power density, efficiency, and linearity in a small, lightweight package.

**FEATURES**

- Over / Under / Reverse Voltage Protection
- High Speed On/Off Control
- Optional Heatsink

APPLICATIONS

- Military / Commercial Data links
- Telecommunications
- BTS / Repeater / DAS
- Test and Measurement
- General Purpose Lab Use

RF / ELECTRICAL


PARAMETER	MIN	TYP	MAX	UNIT
Operating Frequency	30		3000	MHz
P1dB Power Output		36.0		dBm
PSat Power Output	38.0	39.0		dBm
Gain	16.0	17.0		dB
Gain Flatness		0.5	1.3	dB
OIP3		--		
OIP3 Measurement Conditions		--		--
Input Return Loss	11	12		dB
Operating Voltage	28		30	VDC
Current Draw		0.7	0.8	A
Quiescent Current Draw		0.35		A
Switching Time		1	2	mS

MECHANICAL

PARAMETER	VALUE	UNIT
Dimensions (L x W x H)	2.75 x 2 x 0.52	in.
RF Connectors (Input / Output)	SMA-F / SMA-F	--
DC / Control Connector	Feedthru Pins	--
Cooling	Baseplate Conduction - Optional Heatsink Available	--
Mounting	4-40 Thru Holes	--

ENVIRONMENTAL / PROTECTIONS

PARAMETER	MIN	MAX	UNIT
Operating Temp. (Housing Temp.)	-40	+85	°C
Storage Temp Range	-60	+100	°C
Humidity Range	0-100		%
Altitude	0-30,000		ft.
Shock / Vibration	MIL-STD-810 and equivalents		--
Max RF Input	25.0		dBm
Load VSWR @ P1dB	Open / Short Output Protection		--
PA Baseplate Shutoff Temperature	85		°C

OUTLINE DRAWING


DC / CONTROL PINS

PIN LABEL	NAME	DESCRIPTION
+VDC		Supply Voltage - Range Specified in Datasheet
I/O		On / Off Control (+5V = On / 0V = Off)
GND		Ground