

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing



TECHNICAL DATA SHEET

PE44331

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing

Configuration

ConnectorF FemaleConnector Interface TypeThru HoleCable Attachment Method (Shield/Contact)SolderBody StyleStraight

Electrical Specifications

Impedance, Ohms 75

Mechanical Specifications

Size

 Length, in [mm]
 1.04 [26.42]

 Width/Dia., in [mm]
 0.374 [10]

 Height, in [mm]
 0.374 [9.5]

 Weight, lbs [g]
 0.137 [62.14]

Connector

Type F Female
Contact Material and Plating Brass, Tin
Body Material and Plating Brass, Nickel
Dielectric Type PP

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing PE44331

URL: http://www.pasternack.com/f-female-standard-thru-hole-pcb-connector-pe44331-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE44331 CAD Drawing

75 Ohm F Female Connector Solder Attachment Thru Hole PCB, .320 inch x .091 inch Hole Spacing

