

Coaxial

Power Splitter/Combiner

2 Way-0° 50Ω 500 to 2500 MHz

ZX10-2-252+


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1.5W max.
Internal Dissipation (as a combiner)	0.75W max.
Permanent damage may occur if any of these limits are exceeded.	

Coaxial Connections

SUM PORT	3
PORT 1	1
PORT 2	2

Outline Drawing



Outline Dimensions (Inch/mm)


A	B	C	D	E	F	G
.74	.90	.54	.50	.04	.16	.29
18.80	22.86	13.72	12.70	1.02	4.06	7.37
H	J	K	L	M	N	wt
.37	--	.122	.496	.106	.122	grams
9.40	--	3.10	12.60	2.69	3.10	20.0

Features

- wide bandwidth, 500 to 2500 MHz
- excellent amplitude unbalance, 0.02 dB typ.
- very good phase unbalance, 1 deg. typ.
- small size
- low cost
- protected under U.S. Patent 6,790,049

Applications

- PCN
- GPS
- radar
- Cellular
- DCS
- DCS
- GSM
- communications
- WCDMA



CASE STYLE: FL905

Connectors	Model	Price	Qty.
SMA	ZX10-2-252-S+	\$31.95	(1-24)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 3.0 dB		PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)
$f_L - f_U$	Typ.	Min.	Typ.	Max.	Max.	Max.
500-2500	22	10	0.9	1.7	4.0	0.2


Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
500.0	3.67	3.65	0.01	11.62	0.29	1.57	1.27	1.26
700.0	3.62	3.60	0.02	16.70	0.36	1.35	1.18	1.18
900.0	3.59	3.59	0.01	24.57	0.43	1.16	1.12	1.12
1100.0	3.64	3.64	0.00	27.96	0.53	1.09	1.07	1.07
1300.0	3.74	3.75	0.01	22.65	0.61	1.21	1.04	1.04
1500.0	3.87	3.88	0.01	21.54	0.69	1.32	1.10	1.10
1700.0	3.96	3.97	0.01	24.03	0.77	1.34	1.19	1.19
1800.0	3.99	4.00	0.01	27.66	0.82	1.32	1.23	1.23
1900.0	4.01	4.01	0.00	35.60	0.86	1.28	1.27	1.27
2000.0	4.03	4.03	0.00	32.76	0.91	1.21	1.30	1.29
2100.0	4.04	4.04	0.01	24.72	0.96	1.14	1.32	1.31
2200.0	4.06	4.05	0.01	20.20	1.00	1.06	1.32	1.32
2300.0	4.10	4.09	0.02	17.05	1.05	1.06	1.32	1.31
2400.0	4.16	4.14	0.02	14.71	1.07	1.16	1.30	1.30
2500.0	4.24	4.22	0.02	12.86	1.12	1.28	1.28	1.28

1. Total Loss = Insertion Loss + 3dB splitter loss.



electrical schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at www.minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs & shopping online see web site

REV. A
M127604
ZX10-2-252+
ED-13246A/1
DY/CP
120130