



# 50 Ohm 4 Way SMA Power Divider From 500 MHz to 1,000 MHz Rated at 10 Watts

## TECHNICAL DATA SHEET

PE2009

#### 50 Ohm 4 Way SMA Power Divider From 500 MHz to 1,000 MHz Rated at 10 Watts

#### Configuration

Input Connector

Ouput Connectors

SMA Female

SMA Female

Frequency Range, MHz

Number of Output Ports

SMA Female

500 to 1,000

#### **Electrical Specifications**

Frequency Range, MHz 500 to 1,000 Impedance, Ohms 50
Maximum Insertion Loss, dB 0.4
Maximum Input VSWR 1.3:1
Minimum Isolation, dB 20

### **Mechanical Specifications**

#### Size

 Length, in [mm]
 3.5 [88.9]

 Width, in [mm]
 2.5 [63.5]

 Height, in [mm]
 0.375 [9.53]

Compliance Certifications (visit www.Pasternack.com for current document)

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

50 Ohm 4 Way SMA Power Divider From 500 MHz to 1,000 MHz Rated at 10 Watts from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 50 Ohm 4 Way SMA Power Divider From 500 MHz to 1,000 MHz Rated at 10 Watts PE2009

URL: http://www.pasternack.com/4-way-sma-reactive-power-divider-500-mhz-1000-mhz-10-watts-pe2009-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE2009 CAD Drawing
50 Ohm 4 Way SMA Power Divider From 500 MHz to 1,000 MHz Rated at 10 Watts

