



AMP1015 SOLID STATE HIGH POWER AMPLIFIER

PRELIMINARY

FEATURES

Class AB linear GaN design
Instantaneous wide bandwidth
Suitable for all modulations standards
Built-in protection circuits
High reliability and ruggedness

ELECTRICAL SPECIFICATIONS



Parameter	Specification	Notes
Operating Frequency Range	800 - 4200 MHz	
Power Output	50 Watt Min	CW
Power Gain	47 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input / Output VSWR	>10 dB	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	35dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	>20 dBc Typ	At rated Pout
Non Harmonics Spurious	>60 dBc	
Operating Voltage	28 - 30 VDC	
Current Consumption	7 Amp Max	@ 35 Watt
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	$\infty : 1$	
Turn On / Off Speed	5 μSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	188 X 92 X 27	Excluding Connectors
Weight	600 gr.	
RF Connectors In/Out	SMA female	
DC Power / Interface Connector	9-Pin D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	N/C
2	REV	N/C
3	CURRENT SENSOR	$I_D @ 50\text{mV}/100\text{mA}$ Typ
4	TEMP SENSOR	$V_T @ 10\text{mV}/^\circ\text{C} + 500\text{mV}$ Typ
5	SHUTDOWN	TTL
6, 7	VDD	28VDC
8, 9	GND	Ground



AMP1015 SOLID STATE HIGH POWER AMPLIFIER

PRELIMINARY

OUTLINE DRAWING

