




Electrical Characteristics

1. Characteristic Impedance: $50\ \Omega$
2. Frequency range: DC~18Ghz
3. Contact resistance
Center conductor: $\leq 3.0\ m\Omega$
Out conductor: $\leq 2.0\ m\Omega$
4. Insulation resistance: $\geq 5000M\Omega$
5. Insulator withstanding: 1000V
6. Durability: 500cycles

Application: MIL-C-39012/55D

Material&Finishing

1. Center contact :
Female: beryllium coper, gold plated
2. Body: brass, gold plated
3. Insulators: PTFE


主要性能指标

1. 特性阻抗: $50\ \Omega$
2. 频率范围: DC~18Ghz
3. 接触电阻:
中心导体: $\leq 3.0\ m\Omega$
外导体: $\leq 2.0\ m\Omega$
4. 绝缘电阻: $\geq 5000M\Omega$
5. 介质耐压: 1000V
6. 插拔次数: 500次

执行标准: MIL-C-39012/55D

材料和镀层

1. 中心接触件:
插孔: 镀青铜, 镀金
2. 壳体: 黄铜, 镀金
3. 绝缘子: 聚四氟乙烯

		SCALE		SMA-KJK RF COAXIAL CONNECTOR	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE mm, TOLERANCES ARE FRACTIONS DECIMALS ANGLES .X± .15 ±1° .XX± .05 .XXX±
		2.5:1			
	NAME	DATE	西安富士达科技股份有限公司 XI'AN FORSTAR S&T CO.,LTD.		
DRAWN					
CHECKED					
APPROVED					