REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED



SPECIFICATIONS:

FREQUENCY RANGE:	100–700 MHz
COUPLING:	50dB
FLATNESS:	±0.50dB
INSERTION LOSS:	0.15dB Max.
DIRECTIVITY:	20dB Min.
VSWR PRIME LINE:	1.15:1 Max.
POWER:	3,000 Watts CW

MATERIAL:

DRAWN: Paiboon Luekhamhan — DATE: 01–06–2011

APPROVED: T. Nguyen — DATE: 01–06–2011

MCLI
MICROWAVE COMMUNICATIONS LABORATORIES INC.
7255 30TH AVE. N. SAINT PETERSBURG, FL 33710
TEL: (727) 344–6254 FAX: (727) 381–6116
hhtp://WWW.MCLI.COM

UNLESS OTHERWISE SPECIFIED:
TOLERANCES
IN (INCHES) OR [mm] (MILLIMETERS)
FRACTIONS: ± 1/64
DECIMALS: ±.01 ±.005
ANGLE: ±1/2°

PROPRIETARY NOTICE:
THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT WRITTEN PERMISSION FROM MICROWAVE COMMUNICATIONS LABORATORIES INC. (MCLI)

THIRD ANGLE PROJECTION

SCALE: N/A

SHEET: N/A

DRAWING TITLE: HIGH POWER DUAL DIRECTIONAL COUPLER

PART NO. HDL–24–50

CAGE CODE: 0D2L5

SIZE: C

REV: N/A

DO NOT SCALE THE DRAWING

DWG NO. 85217