



	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Production</u>	<u>First Article</u>
	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>	<u>NOTES</u>	<u>Test</u>	<u>Test</u>
Frequency Range	800		1600	MHz	1	<input type="checkbox"/>	<input type="checkbox"/>
Tuning Voltage	0		20	V	1	<input type="checkbox"/>	<input type="checkbox"/>
Modulation Sensitivity	25		65	MHz/V	3	<input type="checkbox"/>	<input type="checkbox"/>
Operates with V <sub>tune</sub> = 0V					3	<input type="checkbox"/>	<input type="checkbox"/>
Output Power	12	15	18	dBm	1	<input type="checkbox"/>	<input type="checkbox"/>
Phase Noise @							
1 KHz Offset		-75		dBc/Hz	2	<input type="checkbox"/>	<input type="checkbox"/>
10 KHz Offset		-100		dBc/Hz	3	<input type="checkbox"/>	<input type="checkbox"/>
100 KHz Offset		-120		dBc/Hz	2	<input type="checkbox"/>	<input type="checkbox"/>
1MHz offset		-140		dBc/Hz	2	<input type="checkbox"/>	<input type="checkbox"/>
Pushing			5	MHz/V	3	<input type="checkbox"/>	<input type="checkbox"/>
Pulling (12 dB R.L.)			15	MHz	3	<input type="checkbox"/>	
Modulation Bandwidth		1		MHz	4		
Tuning Port Capacitance		47		pF	2		
Harmonics		-10		dBc	3	<input type="checkbox"/>	
Sub-Harmonics		N/A		dBc	3	<input type="checkbox"/>	
V <sub>cc</sub>		12.0		V	5	<input type="checkbox"/>	<input type="checkbox"/>
I <sub>cc</sub>		35		mA	5	<input type="checkbox"/>	<input type="checkbox"/>
Operating Temperature	-40		+85	C	3	<input type="checkbox"/>	
Package		SM					
LxW		0.500		inch sq.	5	<input type="checkbox"/>	<input type="checkbox"/>
Height		0.220		inch	5	<input type="checkbox"/>	<input type="checkbox"/>

### Notes

1. Tested in production, and guaranteed
2. Per current design, not a tested parameter
3. Sample tested from production lot
4. Not a tested or guaranteed design goal
5. By inspection